sauermann®



DATA SHEET

Accessories

For manometers

Tubes

Ref.: TC 5 X 8



Clear tube Ø5 x 8, for permanent installation (m/l or 25 m).

Ref.: TS 4 X 7



Silicone tube Ø4 x 7 in black or white, for test instruments (m/l).

Manometer liquids



Ref.: AWS 10 Density = 0.87. Bottles of: 20 ml, 30 ml, 125 ml, 250 ml, 500 ml, 1000 ml.

Ref.: VOLT 1S Density = 1.86. Bottles of : 10 ml, 20 ml, 30 ml, 125 ml.

Ref.: VF1 Density = 1. Bottles of: 20 ml, 30 ml, 125 ml, 250 ml, 500 ml, 1000 ml.

Pressure connections

Ref.: KR 483



Connection kit with 2 quick connections n° 483 and 2 m of clear tube.

Ref.: DP 339



Connection for double-shell wall maximum thickness: 80 mm.
Drilling diameter: 6 mm.

Ref.: 482



Simple conection with rear nut, M5 threading, length 15 mm.
Drilling diameter: 5 mm.

Ref.: DP 447



Connection for double-shell wall, maximum thickness: 30 mm.
Drilling diameter: 6 mm.

Ref.: 483



Quick-connection for wall without rear access.
Drilling diameter: 10 mm.

Ref.: PC 482



Through-connection for partitions standard lengths 35 to 210 mm.
Drilling diameter: 11 mm.

Manometers connections

Ref.: 487



Simple connection in chromed brass for all type of manometers using AWS 10 and VOLT 1S. Thread: 1/8 gas.

Ref.: 505



Valve connection in chromed brass for portable MT, KM, TJ and LU manometer using VOLT 1S liquid. Thread: 1/8 gas.

Ref.: 466



Simple connection in nylon for GF manometers, using VF1 liquid.
Thread: 7 x 100.

Ref.: 509



Chromed brass safety connection, eliminating overspill on manometer using AWS 10 and VOLT 1S.
Thread: 1/8 gas.

Ref.: 666



Male/female, 1/8 connection,
air vent valve with a slide block to set the zero point without disconnecting the tubes.

Ref.: 555 M/F



Male / female, 1/8 gas ball valve, for manometer isolation.

Ref.: 555 F/F



Female / female, 1/8 gas ball valve, for manometer isolation.

Junctions

Ref.: J.D.C

Straight connection
for Ø5 x 8 tube.

Ref.: J.T.C



T-connection
for Ø5 x 8 tube.

Ref.: J.Y.C



Y-connection
for Ø5 x 8 tube.

Accessories

Ref.	Description
494	Pressure tube, length 1 m for MT and KM manometers. With moulded ends
FM-KS.10	Set of 2 magnetic fixings
GPN 900	Plug -8.5 A for all Ø6.2 mm connections. 10 units bag.
ALTU	Altunet cleaning product, 500 ml bottle

FT_EN – Manometers accessories – 06/05/20 – Non-contractual document – We reserve the right to modify the characteristics of our products without prior notice.