Bellows Couplings **HucoFlex K**

Huco Altra Industrial Motion

Bellows Coupling with fixed clamp shaft connection, short version

ORDERING INFORMATION

RS PART No.	MANUFACTURER PART No.	BORES B1 & B2 [mm]
1967714	554.66.4646	19
1967715	554.66.4949	22
1967716	554.66.5454	28
1967717	554.66.5858	32







DIMENSIONS & INTERFACE DATA

Overall Diameter D [mm]	66
Overall Length L [mm]	79
Maximum permissible bore B1. B2 [mm]	32
Length of supported bore L1 [mm]	29
Fastener thread size	M8
Fastener tightening torque [Nm]	40
Coupling approx weight [g]*	390

MATERIALS

Hubs **Aluminium alloy**

Bellows **Spring Quality Stainless Steel**

Fasteners **Alloy Steel**

PERFORMANCE DATA

Maximum speed [min^{-1}]	8700
Peak Torque [Nm]	60
Maximum shaft angular misalignment [deg]	1.5
Maximum shaft radial misalignment [mm]	0.15
Maximum shaft axial displacement [mm]	0.6
Torsional Stiffness [$Nm.rad^{-1}$]	75000
Radial Stiffness [N/mm]	1150
Axial Stiffness [N/mm]	90

Temperature Range

-30°C to +120°C

*weight with max. bore