Specifications

Eaton 269002

Catalog Number: 269002

Eaton Distribution parts, Fuse-link with blink application, D02, 35A, 24 V, gL/gG, set consists of 3 pieces



General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	269002
EAN	**Product Length/Depth**
4015082690021	45 mm
Product Height	**Product Width**
80 mm	54 mm
Product Weight	**Compliances**
0.145 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Z-SLS/CEK
Fuse links
Z-SLK/NEOZ
Z-SLS/NEOZ
Fuse material
Fuse set
Accessory

Type

Accessory
Fuse material
Fuse set

Special features

With flashing function
Snap-fit on DIN rail
1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator

Amperage Rating

35 A

Frame

D02

Equipment heat dissipation, current-dependent

2.8 W

Utilization category

gG (gL)
gL/gG (cable protection/equipment protection)

Color

Black

Ambient operating temperature - max

55 °C

Ambient operating temperature - min

-25 °C

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

Resources

Characteristic curve

1220DIA-7

1220DIA-6

Declarations of conformity

DA-DC-03_Z-S

DA-DC-03_Z-SLS-B

DA-DC-03_Z-S_SC_SB

0 W

Rated operational current for specified heat dissipation (In)

35 A

Rated operational voltage (Ue) - max

24 V

Rated uninterrupted current (Iu)

35 A

Static heat dissipation, non-current-dependent

0 W

Test voltage

5 KV

Voltage rating at AC

24 - 60 V AC

Voltage rating at DC

24 - 60 V DC

Functions

Accessory

Voltage rating

24 V AC - 60 V AC

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia