306A - Click wrenches with removable ratchet



Description:

● Factory accuracy: ± 2% except: - R.306-25D - K306-600D - K306-1000D (± 4%). - R.304DA (± 6%).
● Reliability of mechanism: 50 000 cycles (wrenches up to 200 N.m).
● Use possible with accessories: - End fitting: 9 x 12 or 14 x 18 mm. - Diameter: 30 mm.
● One-way wrenches usable for unscrewing by reversing the bits.
● Numbered wrenches supplied with ISO 6789 calibration certificate.
● Supplied in a plastic box with ratchet and hinged handle (except Ref R.306A25 - R.301A - K.306A600 - K.306A1000).

© FACOM 2020

	Length L [mm]	Attachement ["]	Capacity [Nm]	Graduation [Nm]	Weight [Kg]	Contents []
J.306A100	437.0	9 x 12	20 - 100	1.0	1	Tray: PL.352A
J.306A50	357.0	9 x 12	10 - 50	1.0	0,93	Roll: N.38A-9E
K.306A600	990.0	14 x 18	120 - 600	2.0	5,2	
R.301A	185.0	9 x 12	1 - 5	0.05	0,29	Box
R.306A25	271.0	9 x 12	5 - 25	0.1	0,45	Box
S.306A100	437.0	9 x 12	20 - 100	1.0	1	
S.306A200	515.0	14 x 18	40 - 200	1.0	1,3	
S.306A350	725.0	14 x 18	70 - 350	2.0	1,8	

© FACOM 2020