Your Expert Partner for **Human Machine Interfaces**

Illumination element

Distribution by
Rs-online

45-320.2G11



https://rs-online.eao.com/component/45-320.2G...

Your product:



45-320.2G11
Illumination element

MOUNTING

Component mounting type: Base mounting

OPERATING-/INDICATION PART

Illumination colour: Yellow

ELECTRICAL CHARACTERISTICS

Operating voltage: 6 - 24 V AC/DC

Surge voltage resistance: 4 kV

Lumi. Intensity: 900 - 1400 mcd

MECHANICAL CHARACTERISTICS

Terminal: Screw terminal

Terminal details 1: Solid 2 x (1.0 … 1.5mm^2)
– With end sleeves 2 x (0.5 … 0.75 mm^2)

Terminal details 2: Finely stranded
– Without end sleeves 2 x (0.5 … 0.75 mm^2)
– Without end sleeves 2 x (0.5 … 1.5 mm^2)
– For AWG cables for auxiliary contacts 2 x (18 … 14)

Weight: 0.02 kg

CERTIFICATE

REACH: REACH compliant


RoHS: RoHS compliant

OTHER

Short Description: Illumination element, Screw terminal, Yellow, 6 - 24 V AC/DC, Base mounting

Hints: Illumination element base mounting can used only with enclosure

Wiring diagrams:



Dimension drawings:

