Handling protection

ULTRANE 500

Grip and skin protection for oily environments.



GRIP & PROOF TECHNOLOGY

EN388	EN407	
4121A	X1XXXX	ISO 18889
CATEGORY 3	ISO 13997:	DEXTERITY
CE 0334	4.9 N	EN ISO 21420: 5/5

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

SPECIFIC ADVANTAGES

Durability

- Color adapted to dirty environements for a prolonged durability.
- Excellent abrasion resistance due to the nitrile coating

Productivity

- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Oilproof, it repels oil penetration and reduce dermatitis

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

- Washable 3 times at 40°, to extend lifespan, reduce costs and waste

Additional benefits

- Available in vending machine packaging

Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive/mechanical industry
- Other industries
- Glass industry
- Agriculture sector

APPLICATIONS

- Handling glass sheets
- Re-entry tasks
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil

Edit 01/12/2024

Handling protection

ULTRANE 500

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	1	2	1	A	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread



ISO 18889

PROTECTION FROM PESTICIDES
GR: Re-entry tasks

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.1E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.4E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953 Update 01-07/09/2023
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 01/12/2024