Rittal – The System.

Faster – better – everywhere.

TopTherm wall-mounted cooling unit Blue e Total cooling output 1.00 - 1.50 kW – SK 3304.510

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TopTherm wall-mounted cooling unit Blue e Total cooling output 1.00 - 1.50 kW – SK 3304.510

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Energy-efficient Blue e wall-mounted cooling units with integral e-Comfort controller, RiNano coating on the condenser and electrical condensate evaporation as standard.
Benefits:	May be linked to the IoT interface via the Blue e IoT adaptor
Material:	Sheet steel
Colour:	RAL 7035
Protection category IP to IEC 60 529:	External circuit IP 34 Internal circuit IP 54
Supply includes:	Nano-coated condenser Integral electric condensate evaporation Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts

Product description

Variant:	wall-mounted
Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 1.1 kW L 35 L 35 at 60 Hz: 1.25 kW L 35 L 50 at 50 Hz: 0.91 kW L 35 L 50 at 60 Hz: 0.9 kW
Air throughput (unimpeded air flow):	External circuit: 805 m³/h Internal circuit: 600 m³/h

Rated operating voltage:	115 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 400 mm Height: 950 mm Depth: 260 mm
Temperature control:	e-Comfort controller (factory setting +35 °C)
Temperature range:	Bearing: -40 °C...+70 °C Operation (environment): +10 °C...+55 °C Setting range: +20 °C...+55 °C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 0.32 kg Global Warming Potential (GWP): 1430 CO_2 equivalent (CO_2e): 0.46 t
Power consumption P_{el}:	L 35 L 35 at 50 Hz: 0.64 kW L 35 L 35 at 60 Hz: 0.68 kW L 35 L 50 at 50 Hz: 0.71 kW L 35 L 50 at 60 Hz: 0.81 kW
Rated current max.:	At 50 Hz: 8 A At 60 Hz: 8.8 A
Start-up current max.:	At 50 Hz: 26 A At 60 Hz: 28 A
Pre-fuse:	Transformer circuit-breaker: 11 A...16 A
Permissible operating pressure (p. max.):	28 bar
eCl@ss 8.0/8.1:	27180704
Energy efficiency ratio (EER) 50/60 Hz L35 L35:	1,83 / 1,84
Packs of:	1 pc(s).
Weight/pack:	44 kg
EAN:	4028177322929
Customs tariff number:	84158200
ETIM 7.0:	EC000855
ETIM 6.0:	EC000855

eCl@ss 8.0/8.1:	27180704
eCl@ss 6.0/6.1:	27180704
Product description:	SK cooling unit Blue e, wall-mounted, 1.1 kW, 115 V, 1~, 50/60 Hz, Sheet steel, WHD: 400 x 950 x 260 mm

Approvals

Approvals:	Approval overview CCC exception letter CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation FCC