DATASHEET - M22-WRJS2H

Joystick, with one operating point per operating direction, with metal shaft, 2 positions, Bezel: titanium, maintained, Horizontal

Powering Business Worldwide

Part no. **M22-WRJS2H**
178574

Product name	Eaton Moeller® series M22 Joystick
Part no.	M22-WRJS2H
EAN	4015081739035
Product Length/Depth	100 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.038 kilogram
Certifications	CSA-C22.2 No. 14-13 UL File No.: E29184 VDE 0660 CSA UL Category Control No.: NKCR CSA Class No.: 3211-03 UL 508 IEC/EN 60947-5 CE IEC/EN 60947 CSA File No.: 012528 UL CSA-C22.2 No. 94-91
Product Tradename	M22
Product Type	Joystick
Product Sub Type	None
Bezel color	Titanium
Bezel material	Plastic
Fitted with:	Front ring Filament bulb (24 V) Metal shaft
Degree of protection	IP66 NEMA 4X, 13
Lifespan, mechanical	100,000 Operations
Opening diameter	22.5 mm
Operating frequency	2000 Operations/h
Type	Joystick
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Rated operational current (Ie) at AC-21, 400 V, 415 V	0 A
Connection to SmartWire-DT	With SWD-RMQ connections Yes
Actuating force	5 N
Actuator function	Maintained Horizontal
Number of actuation directions	2

Force for positive opening - min			0 N

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Control switch, Joystick (EC000632)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Control switch, joystick (ecl@ss10.0.1-27-37-14-04 [AKF061013])

Rated operation current Ie at AC-21, 400 V		A	0
Centre mounting, hole diameter		mm	22.5
Joy stick length		mm	75
Number of actuation directions			2
Number of switch positions			0
Number of normally open contacts per actuation direction			0
Number of normally closed contacts per actuation direction			0
Number of make-and-break contacts per direction			0
With retraction in 0-position			No
Locking in 0-position			No
Coder			No
Analogue output signal configurable			No
With front ring			Yes
Material front ring			Plastic
Colour front ring			Titanium
Degree of protection (IP)			IP66
Degree of protection (NEMA)			4X, 13

© 04/2023 by Eaton Industries GmbH