
JxxXxxXyyDzzz

Optical UPC zipcord duplex LSZH patchcords



P/N: JSCSC2DOS2
SC/SC duplex yellow patch cord OS2
Duplex clip included (Other connectors available)




Optical fiber
2x9 / 125 µm

Secondary Coating
Color : white and orange
Diameter : 900 µm
Semi-tight buffered version

Strenght Members
aramid yams

Common Outer Sheath colors :
yellow - SM, (AQUA - OM3,
AQUA or ERICA VIOLET- OM4)
dimension : 2.8mm x 5.6mm
material : LSHZ compround



Fiber cable construction

DESCRIPTION / APPLICATIONS

MMC optical patchcords are ideal for all singlemode and multimode applications. These patchcords are a part of the complete optical link and suit all type of networks, like Telecom, LAN (local Area Network), Wan (Wide Area Network) and MAN (Metropolitan Area Network).

GENERAL CHARACTERISTICS

- Optically and mechanically compatible with all the equivalent connectors.
- Optical patch cords with 4 connectors with ceramic ferrule (ZrO_2) and composite body (SC, LC) or metal (ST,FC)
- Duplex optical patch cords
- Duplex LSZH sheath with aramid yarns strength members (Kevlar-type)
- Individual test report and unit packaging
- Available in different lengths

STANDARDS

- **IEC 60874-14, IEC 61754-2, -4, -4-7, -4-8, -13, -20, -20-7, -20-8,**
- **IEC 793, IEC 794-1-E1, IEC 794-1-E3,**
- **ITU-T G.652D,**
- **UL 1666/901 (WHEN UL CABLE IS USED AND TIA/EIA 455)**
- **ISO/IEC 11801 2ND ED. AMS 1.0, AMD 2.0**
- **JIS C5973 F04, ICEA-596**
- **BELLCORE/TELCORDIA GR-326, GR-409-CORE**
- **TIA/EIA 604-3, TIA/EIA 568, EN 50173**
- **ROHS COMPLIANCE ON ALL COMPONENTS AND FINAL PRODUCT,**
- **WITH NO HAZARDOUS SUBSTANCES AS DETAILED IN ROHS 2002/95/EC**

This document is confidential and is the property of MultiMedia Connect. MultiMedia Connect owns a copyright and the document must not be copied or modified in any other form, in whole or in part without written permission from MMC The characteristics given in this document are not contractual and are subject to change without notice.

PATCH CORDS GENERAL CHARACTERISTICS

Temperature range	- 20°C to +60°C(OM3,OM4, OM5,OS2) - 5°C to +60°C
Mating cycles	> 500 cycles
Colour of sheath	Yellow (OS2) | Aqua (OM3) | Erika Violet (OM4)
Fiber version	3mm (OM3, OM4,OM4A,OS2) | 3mm (ST & SC)
Colour of boots	Black & Red (ST & SC) White(LC)(OM3, OM4,OM4A) | Green & Black (OS2APC) | Blue & Black (OS2)
Return Loss	> 20dB (OM3,OM4) | > 40dB (OS2)
Insertion Loss (Attenuation)	< 0.3 dB(OM3,OM4,OS2) | < 0.25dB (OM4A)

CONNECTORS TECHNICAL CHARACTERISTICS

Types	SC, LC (other on request)
Material of ferrule	ZrO_2 (Zirconia / Ceramic)
Connector surface	Convex
Fiber's connection	Epoxy
Material of body	Metal (ST, FC) or composite (SC, LC, MU)
Ferrule drilling	125/126µm (OS2) | 127/128µm (OM3,OM4)

OPTICAL CABLE MECHANICAL PROPERTIES

Weight	15 kg/km
Temperature range	-20°C to +60°C (-5°C to +70°C OM4)
Bending radius	40 mm
Tensile strength	250N (long term) – 450N (short term)
Crush resistance	1000N/dm (OM3,OM4,OS2) | 2000N/dm (OM4)

This document is confidential and is the property of MultiMedia Connect. MultiMedia Connect owns a copyright and the document must not be copied or modified in any other form, in whole or in part without written permission from MMC The characteristics given in this document are not contractual and are subject to change without notice.

OPTICAL CABLE PERFORMANCES

Parameters		OM3	OM4	OS2
Core diameter	µm	50	50	9
Cladding diameter	µm	125	125	125
Typ. Attenuation @ 850nm	dB/km	≤ 2.7	≤ 2.7	≤ 0.35
Typ. Attenuation @ 1300nm	dB/km	≤ 0.8	≤ 0.8	≤ 0.22
Bandwidth @ 850nm	MHz * km	> 1500	> 3500	
Bandwidth @ 1300nm	MHz * km	> 500	> 500	
EMB* @ 850nm	MHz * km	> 2000	> 4700	
Chromatic dispersion @1285-13300nm	Ps/(nm*km)			≤ 0.35
Chromatic dispersion @ 1550nm	Ps/(nm*km)			≤ 0.22

ORDERING INFORMATION

Part Numbers structure	JxxX xxX yyy Dzzz
Replace xx by the connectors left/right	Standard UPC connectors are : SC, LC (others on request)
Replace X by A for APC	Standard APC 8° connectors are: SC, LC, FC
Replace yyy by the length in meters	From 1 up to 100 meters
Replace zzz the type of fiber	OM3 , OM4 ,OS2
Standard lengths (other lengths on request)	1m / 2m / 3m / 5m / 10m / 15m / 20m / 25m / 30m / 50m / 100m

This document is confidential and is the property of MultiMedia Connect. MultiMedia Connect owns a copyright and the document must not be copied or modified in any other form, in whole or in part without written permission from MMC The characteristics given in this document are not contractual and are subject to change without notice.