TECHNICAL SPECIFICATION

EVO® Gas Goggle

Clear with MistResist™ coating / AGM030-623-000



DESCRIPTION

Engineered to offer outstanding performance, compatibility and comfort, with the option to fit an RX insert enabling safe use of prescription lenses. The EVO® Gas Goggle is suitable for protection against gas and fine particles, and features NBR foam surround for enhanced comfort and fit.

OPTIONS

Clear with MistResist™ coating (AGM030-623-000)

SAFETY STANDARDS

EN 166 • EN 170

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacturer's Trademark
JSP Dagger

Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B

Protection from Liquid Droplets
3

Protection from Gas and Fine Particles (below 40 um grain size)
5

Resistance to fogging (optional)
N

Product Weight
100g

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Protection from Large Dust Particles (up to 40 um grain size)
4

Resistance to Molten Metals and Hot Solids Helmets (optional)
9

RX Insert
Optional

FEATURES



Compatibility

Low profile design means the EVO® Goggle can be worn with an industrial safety helmet or bumpcap.



Comfort

Foam surround on the goggle housing for comfort and to ensure a good fit across a wide range of facial profiles.



RX Inserts

RX inserts are available for the EVO® Goggle range, for combined prescription and safety eyewear. Inserts can be taken to an optician for glazing with corrective lenses.



Non-Vented

Non-vented goggle body for gas and fine particle protection.

RANGE

evoGoggle evolution

DOWNLOADS

Image Pack (ZIP)
doc-evo-gas-goggle.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.