9531021 | Set of 2 Standard hand taps HSS -BSP G -DIN 352 -Stepped profile

Manual tapping of steels.





- **Threading of standard Steels**
- **Gradual work**
- High-speed steel

Machine



Application



P1- Unrealized steels

Features



Properties and benefits

✚ High-speed steel: HSS substrate ⛑ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	l	l4	l5	QTY	PCB
953102100180280	8420609252716	BSPG	1/8"	28	DIN 5157	8,80	63	18	2 > 6.5	5,50	2	1
953102100140190	8420609252709	BSPG	1/4"	19	DIN 5157	11,80	70	20	2 > 6.5	9,00	2	1
953102100380190	8420609252730	BSPG	3/8"	19	DIN 5157	15,25	70	20	2 > 6.5	9,00	2	1
953102100120140	8420609252693	BSPG	1/2"	14	DIN 5157	19,00	80	22	2 > 6.5	12,00	2	1
953102100580140	8420609252747	BSPG	5/8"	14	DIN 5157	21,00	80	22	2 > 6.5	14,50	2	1
953102100340140	8420609252723	BSPG	3/4"	14	DIN 5157	24,50	90	22	2 > 6.5	16,00	2	1
953102100780140	8420609252754	BSPG	7/8"	14	DIN 5157	28,25	90	22	2 > 6.5	18,00	2	1
953102110000110	8420609252761	BSPG	1"	11	DIN 5157	30,75	100	25	2 > 6.5	20,00	2	1
953102110140110	8420609252785	BSPG	1"1/4	11	DIN 5157	39,50	125	32	2 > 6.5	24,00	2	1
953102110380110	8420609252815	BSPG	1"3/8	11	DIN 5157	42,00	125	32	2 > 6.5	29,00	2	1
953102110120110	8420609252778	BSPG	1"1/2	11	DIN 5157	45,50	140	32	2 > 6.5	29,00	2	1
953102120000110	8420609252822	BSPG	2"	11	DIN 5157	57,20	160	36	2 > 6.5	35,00	2	1
953102110180110	8420609252792	BSPG	1" 1/8	11	DIN 5157	35,50	125	32	2 > 6.5	22,00	1	1