Domestic fuse carriers


0 058 11


0 058 14


0 058 21


0 058 24

Dimensions **see e-catalogue**

With label-holders
With insulated carrier class II, padlockable
Coupling via supply busbars
Shielded terminals capacity 2 x 10 mm²
Possibilty to signal indicator blown fuse
Fuse not supplied

For domestic cylindrical cartridge fuses

Conform to EN 60269-1 and IEC 60269-1,3

Single pole

Pack	Cat.Nos	For domestic cartridges	Cartridge dimensions (mm)	Number of modules
10	0 058 10	10 A - 230 V~	8.5 x 23	1
10	0 058 11	16 A	10.3 x 25.8	1
10	0 058 12	20 A - 400 V~	8.5 x 31.5	1
10	0 058 13	25 A	10.3 x 31.5	1
10	0 058 14	32 A	10.3 x 38	1

Single pole + neutral

10	0 058 20	10 A - 230 V~	8.5 x 23	1
10	0 058 21	16 A	10.3 x 25.8	1
10	0 058 22	20 A - 400 V~	8.5 x 31.5	1
10	0 058 23	25 A	10.3 x 31.5	1
10	0 058 24	32 A	10.3 x 38	1

For miniature cylindrical cartridge fuses

Conform to EN 60127-6 and IEC 60127-6
To protect sensitive equipment:
transformers, electronic equipment, etc.

Single pole

Pack	Cat.Nos	Cartridge dimensions (mm)	Voltage	Number of modules
5	0 058 00	5 x 20	250 V~	1

Single pole + neutral

5	0 058 02	5 x 20	250 V~	1

Domestic cartridge fuses


0 102 63


0 103 06


0 113 10


0 117 16


0 124 20


0 126 25


0 134 32

Miniature type 5 x 20

Instant reaction fuse - Ceramic body
Conform to EN/IEC 60127-2
High rupture capacity (A)
For use with dimmers, Viking terminal blocks and emergency lightning units, transformers

Pack	Cat.Nos	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)
10	0 102 02	0.2		
10	0 102 05	0.5		
10	0 102 06	0.63		
10	0 102 10	1		
10	0 102 20	2	250	1500
10	0 102 30	3.15		
10	0 102 50	5		
10	0 102 63	6.3		
10	0 102 96[1]	10	250	500

Cylindrical

Pack	Cat.Nos Without indicator	Cat.Nos With indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps) Copper	Protected section (mm²)	Color Indication
6.3 x 23							
10	0 103 06[2]		6	230	6000	1.5	
8.5 x 23							
10		0 114 06	6	230	6000		
10|100	0 113 10	0 114 10	10			1.5	
10.3 x 25.8							
10	0 116 10[2]		10	230	6000		
10	0 116 16[2]	0 117 16[2]	16			2.5	
8.5 x 31.5							
10|100	0 123 20	0 124 20	20	400	20000	2.5	
10.3 x 31.5							
10	0 126 16		16				
10	0 126 20		20	400	20000		
10	0 126 25	0 127 25	25			4	
10.3 x 38							
10|100	0 133 32		32	400	20000		
10		0 134 32	32			6	

Neutral links

Pack	Cat.Nos	
10	0 123 00	8 x 32 (previously 8.5 x 31.5)
10	0 133 00	10 x 38

1: Overrating not described by standarts
2: Conform to BS 1361 (1971)