Handling protection

# ULTRANE 527




RESICOMFORT TECHNOLOGY

MAPA PROFESSIONAL PATENT PENDING TECHNOLOGY

| EN388 | EN407 | CAT.2 |
|---|---|---|
| 31X1A | X1XXXX | CE |

DEXTERITY

EN 420: 5/5

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 CQ 979/2 IFTH
Tested for harmful substances.
www.oeko-tex.com/standard100

## Detachable fingers to limit the risk of entanglement by a rotating tool - MAPA Patent Pending
## Comfort, suppleness and high dexterity without any compromise on breathability and durability

## SPECIFIC ADVANTAGES

### Protection against risk of entanglement
- Detachable fingers to avoid hand risk - Patent Pending

### Comfort
- High suppleness and flexibility dexterity at fingertips proven breathability

### Durability
- Extended use guaranteed by our exclusive process RESICOMFORT. Proven breathability, flexibility and durability of the coating.

### Skin protection
- Free of harmful substances: STANDARD 100 by OEKO-TEX®, DMF Free
- Dermatologically approved

### Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### Washability
- Washable 1 time at 40°C without any alteration on performances*.

## INDUSTRIES
- Automotive/mechanical industry
- Mechanical industry
- Aeronautics industry
- Manufacturing
- Industrial maintenance

## APPLICATIONS
- Mechanical maintenance
- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners

Edit 23/03/2022

Handling protection

# ULTRANE 527

## LEGENDS

EN388 MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

| 3 | 1 | X | 1 | A | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

| X | 1 | X | X | X | X |
|---|---|---|---|---|---|
| 0-4 | 0-4 | 0-4 | 0-4 | 0-4 | 0-4 |

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Seamless textile support |
| Gauge | 15 |
| Exterior finish | Ventilated back |
| Material | Nitrile foam sandy |
| Cuff characteristic | Knitted Cuff |
| Colour.s | Black Grey |
| Size | 6 7 8 9 10 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 270000000000 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 8.2E+11 Ω |

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 1 pair/bag<br>12 pairs/bag<br>96 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/20/3017
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

* Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

Edit 23/03/2022