DATASHEET - XV-152-D4-57TVR-10

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, (PLC)

Part no.	**XV-152-D4-57TVR-10**
	150526
EL Number (Norway)	**4521141**

Product name	Eaton XV-152 Touch panel
Part no.	XV-152-D4-57TVR-10
EAN	7640130097100
Product Length/Depth	212 millimetre
Product height	52.5 millimetre
Product width	156 millimetre
Product weight	1.3 kilogram
Certifications	EN 60950 ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x) UL 60950 IEC/EN 60950 IEC/EN 61241-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x) CSA File No.: UL report applies to both US and Canada CSA Class No.: none Security: EN 50178 IEC/EN 61241-1 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x) IEC/EN 61131-2 CULus UL Category Control No.: NRAQ Certified by UL for use in Canada UL UL508 DNV GL CUL508 IEC/EN 61000-6-4 UL 508 UL File No.: E205091 IEC/EN 61131-2, CE IEC/EN 61000-6-2 IEC/EN 61000-6-3 IEC/EN 60079-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x) EAC
Product Tradename	XV-152
Product Type	Touch panel
Product Sub Type	None
Catalog Notes	4-wire Technology 7 W for basic device + 2.5 W for USB module Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT Heat dissipation with power consumption for 24 V License certificates for onboard interfaces not required Optionally with SD card -> article no. 139807
Enclosure material	Metal, anodized
Features	Ethernet interface UL508, cUL approvals Fanless CPU and system cooling, natural convection-based passive cooling Portrait format Slot for SD card USB device USB Host Overload proof
Fitted with:	1 x USB host 2.0 (built-in interface) Message system (incl. buffer and confirmation) 1 x USB device (built-in interface) 1 x Ethernet 10/100 Mbps (built-in interfaces) Numeric keyboard Recipes 1 x RS485 (built-in interface) Color display 1 x RS232 (built-in interface) Message indication SW interfaces Alpha numeric keyboard Printer output
Functions	Additional software components, loadable Process value representation (output) possible Process default value (input) possible

Battery runtime	Back-up of real-time clock: CR 2032 (190 mA/h), zero maintenance (soldered)
Current consumption	0.4 A, continuous current, Power Supply, 24 V DC
Degree of protection	IP20, rear IP20 NEMA 4X
Degree of protection (front side)	NEMA 4X IP65
Fuse type	Built-in fuse (not accessible)
Lifespan	40,000 h (Service life of back-lighting)
Model	Metal enclosure and front plate
Mounting method	Flush mounting - Inclination from vertical: ±45° (if using natural convection) Flush mounting - Clearance: Width x Height x Depth ≥ 30 mm (1.18") Flush mounting
Product category	HMI-PLC (SPS function, retrofittable)
Repetition rate	1 s
Residual ripple	≤ 5 % (input voltage)
RoHs conformity	Yes
Short-circuit protection	No, external fuse FAZ Z3, Supply voltage UAux Yes, Short-circuit rating, SmartWire-DT supply voltage
Software	XSOFT-CODESYS-2, Visualisation software, Engineering GALILEO, Visualisation software, Engineering XSOFT-CODESYS-3, Visualisation software, Engineering XSOFT-CODESYS-3, PLC-Programming software, Engineering EPAM, Visualisation software, Engineering XSOFT-CODESYS-2, PLC-Programming software, Engineering
Terminal capacity	0.25 - 1.5 mm^2, flexible with ferrule 0.2 - 1.5 mm^2, solid 24 - 16 AWG, solid or stranded
Voltage type	DC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27
Vibration resistance	According to IEC/EN 60068-2-6
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	0 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-20 °C
Ambient storage temperature - max	60 °C
Operating temperature - min	0 °C
Operating temperature - max	50 °C
Relative humidity	10 - 95 % (non-condensing) IEC/EN 50178
Voltage dips	≤ 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (19.2 V DC) ≤ 10 ms, Bridging voltage dips
Inrush current	12.5 A (for 6 ms)
Permissible voltage	19.2 - 30 V DC, effective (rated operating voltage -20 %/+25 %) 35 V DC (for a duration of < 100 ms) 18.0 - 31.2 V DC, absolute with ripple 18 - 31.2 V DC, battery powered (rated operating voltage -25 %/+30 %)
Power consumption	9.5 W total Max. 7 W 2.5 W (USB Slave to USB Host)
Rated control supply voltage	24 V DC (UAUX, -20 %/+25 %) 24 V DC (UPOW, -20 %/+25 %)
Rated operational current (Ie)	0.7 A
Rated operational voltage	14.5 V (± 3 % - SmartWire-DT) 24 V DC (power-supply - safety extra low voltage)
Supply current	0.7 A, Imax, SmartWire-DT supply 3 A, Imax, Supply voltage UAux
Supply voltage at AC, 50 Hz - min	0 V AC
Supply voltage at AC, 50 Hz - max	0 V AC

Supply voltage at DC - min	20.4 V DC
Supply voltage at DC - max	28.8 V DC
Addressing	Address set automatically
Connection	SmartWire-DT blade terminal SWD4-8MF2
Connection type	SWD: Plug, 8-pole Push in terminals, Supply voltage
Data transfer rate	125 kBit/s, SmartWire-DT 250 kBit/s, SmartWire-DT
Interfaces	USB 2.0 device (not galvanically isolated) Ethernet (100Base-TX/10Base-T)
LED indicator	Status indication of SmartWire-DT master: Green and red LEDs Status indication of SmartWire-DT network: Configurable green or red LED Status indication of Supply voltage: LED
Number of slots	1 (for SD-Card)
Number of SmartWire-DT slaves	58
Protocol	TCP/IP EtherNet/IP Other bus systems MODBUS
Station	SmartWire-DT master, SmartWire-DT network
Display contrast ratio	300:1
Display lighting	LED Dimmable via software
Display size	115 x 86 mm
Display type	TFT Standard front with standard membrane (fully enclosed) Color display, TFT
Luminance intensity	250 cd/m²
Number of colors of the display	65536
Screen size (diagonal)	5.7 in
Touch technology	Touch sensor (glass with foil), Resistive touch protective screen Glass with film touch sensor Resistive touch
Resolution	640 x 480 px VGA
Explosion safety category for dust	ATEX dust-ex-protection, in relation to CE ATEX dust-ex-protection, II 3D Ex II T70°C IP5x: Zone 22, Category 3D
Potential isolation	UAUX: no Power supply: no Between UPow and 15 V SmartWire-DT supply voltage: no
Protection against polarity reversal	Yes Yes, for supply voltage (Siemens MPI optional)
Backup time	10 years, typ. (time at zero voltage)
Memory	SD Memory Card Slot: SDA Specification 1.00 (External) NVRAM (Retain data): 125 kByte NAND-Flash (can be used for data backup): approx. 64 MByte available 64 MByte internal DRAM (OS, Program and data memory) NOR-Flash: 2 MByte
Memory capacity	64,000 kByte
Operating system	Windows CE 5.0 (license included)
Processor	RISC CPU, 32 Bit, 400 MHz
Equipment heat dissipation, current-dependent Pvid	9.5 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	9.5 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Graphic panel (EC001412)		
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Graphic panel (HMI) (ecl@ss10.0.1-27-33-02-01 [AFX016003])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20.4 - 28.8
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		1
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		1
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		2
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces other		0
With SW interfaces		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes

Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		Yes
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
Type of display		TFT
With colour display		Yes
Number of colours of the display		65,536
Number of grey-scales/blue-scales of display		0
Screen diagonal	inch	5.7
Number of pixels, horizontal		640
Number of pixels, vertical		480
Useful project memory/user memory	kByte	64,000
With numeric keyboard		Yes
With alpha numeric keyboard		Yes
Number of function buttons, programmable		0
Number of buttons with LED		0
Number of system buttons		1
Touch technology		Resistive touch
With message indication		Yes
With message system (incl. buffer and confirmation)		Yes
Process value representation (output) possible		Yes
Process default value (input) possible		Yes
With recipes		Yes
Number of password levels		200
With printer output		Yes
Number of online languages		100
Additional software components, loadable		Yes
Degree of protection (IP), front side		IP65
Degree of protection (NEMA), front side		4X
Operating temperature	°C	0 - 50
Rail mounting possible		No
Wall mounting/direct mounting		No
Suitable for safety functions		No
Width of the front	mm	212
Height of the front	mm	156
Built-in depth	mm	47

© 04/2023 by Eaton Industries GmbH