To give you the best possible experience, this site uses cookies. By continuing to use the site, or by staying here, you agree to our use of cookies in line with our Privacy Policy. Learn more including how to manage cookies here.

Quick Coupling with ISO 6150 B Profile, Series 30

Part #: 30KATF08SPN



Quick coupling system with nominal diameter 8.5 for pneumatic and fluid handling applications up to 35 bar. Coupling system with ISO 6150 B profile and according to US MIL-SPEC 4109. Available made of brass/steel.

View Series Page Share / Email Print

Technical Specifications

Diameter:	8,5 nom	Hose I.D.:	8
Valve Included:	Yes	Maximum Operating Temperature:	100 °C
Version:	Single Shut-Off	Maximum Operating Pressure:	35 bar
Length:	66 mm	Flow Rate:	890 L/min
Hex Size:	21 mm	Material:	Brass / Steel nickel plate
Outside Diameter:	30 mm	Connection Type:	Hose Barb
Seal Material:	NBR	Type:	Coupling
Minimum Operating Temperature:	-20 °C	Connection Thread Size (inch):	na

Safety Warning

Item Information

Parker's Series 30 is a robust steel coupling 3/8" according to ISO 6150 B and US MIL-SPEC 4109. The coupling system stands out for its very robus design with steel valve bodies. The high insertion depth is guaranteed by an optimized plug guide.

Markets:
- Machinery Construction
- Automotive

Features/Benefits:
- Coupling system according to ISO 6150 B and US MIL-SPEC 4109
- Robust design with steel valve bodies

Applications:
- Pneumatic Power Tools
- Assembly Lines
- Air compressors

CAD Drawings + Files

Related Documents

Parker Sales Company UK

psc.uk.webform@support.parker.com
+44 (0)1926 317878

+ Company Information
+ Global Operations
+ Help & Support
+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.