Date: 11/04/2023

APRPP2"-PPK5/T15-L775/16-PP55R

APRPP2"-PPK5/T15-L775/16-PP55R

Item number: 48783209

Quantity: 1 pcs.

Order code: FLR-CMZA1000M4P2ZZGFZZ07750050NZZ KGOAR5A0675ZZ

Overview:

APRPP2"-PPK5/T15-L775/16-PP55R
Magnetic Level Transmitter Type FLR-PB
Pressure: max. 3 bar
Temperature range 0°C up to 60°C
Fluid density: 1000 kg/m³
Material: Polypropylene (PP)
Housing: Polyester
Ingress protection: IP65
Electrical connection: M20 x 1.5 mm with cable gland
Output signal: 4-20 mA
Head mounted transmitter: T15.HZ - 2 wire, standard
Process connection: Mounting thread downwards 2"BSP
Float: Polypropylene PP55R; Float outer diameter: 55 mm
Guide tube: OD 16 mm Insertion length (L): 775 mm
100% level position (L1): 50 mm
Measuring range: 675 mm
Contact separation: 5 mm

Float fits through the connection nozzle

Details:

APRPP2"-PPK5/T15-L775/16-PP55R
Magnetic Level Transmitter Type FLR-PB
Pressure: max. 3 bar
Temperature range 0°C up to 60°C
Fluid density: 1000 kg/m³
Material: Polypropylene (PP)
Housing: Polyester
Ingress protection: IP65
Electrical connection: M20 x 1.5 mm with cable gland
Output signal: 4-20 mA
Head mounted transmitter: T15.HZ - 2 wire, standard
Process connection: Mounting thread downwards 2"BSP
Float: Polypropylene PP55R; Float outer diameter: 55 mm
Guide tube: OD 16 mm Insertion length (L): 775 mm
100% level position (L1): 50 mm
Measuring range: 675 mm
Contact separation: 5 mm

Float fits through the connection nozzle

© 2023 - WIKA Instruments s.a.r.l.