# S403E-B20

## General Information

| | |
|---|---|
| **Extended Product Type:** | S403E-B20 |
| **Product ID:** | 2CCS553001R0205 |
| **EAN:** | 7612270102587 |
| **Catalog Description:** | S403E-B20 Miniature Circuit Breaker 3 Poles B Characteristic 20A 6000 ~230/400V |
| **Long Description:** | S403E-B20 Miniature Circuit Breaker 3 Poles B Characteristic 20A 6000 ~230/400V |

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Plug-in Distribution Systems

## Ordering

| | |
|---|---|
| **EAN:** | 7612270102587 |
| **Minimum Order Quantity:** | 1 piece |
| **Customs Tariff Number:** | 85363020 |

## Dimensions

| | |
|---|---|
| **Product Net Width:** | 91 mm |
| **Product Net Height:** | 91 mm |
| **Product Net Length:** | 82 mm |
| **Product Net Weight:** | 0.401 kg |

## Container Information

| | |
|---|---|
| **Package Level 1 Units:** | 3 piece |
| **Package Level 1 Width:** | 185 mm |
| **Package Level 1 Height:** | 89 mm |
| **Package Level 1 Length:** | 101 mm |
| **Package Level 1 Gross Weight:** | 1.32 kg |

## Environmental

| | |
|---|---|
| **RoHS Status:** | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

## Additional Information

| | |
|---|---|
| **Frequency (*f*):** | 50 … 60 Hz |
| **IIT Publishing Status:** | Level 0 - Information enabled |
| **Number of Poles:** | 3 |
| **Power Loss:** | 4.8 W |
| **Product Main Type:** | S403 |
| **Product Name:** | Plug-in Distribution Systems |
| **Rated Current ($I_n$):** | 20 A |
| **Rated Operational Current ($I_e$):** | 20 A |
| **Rated Operational Voltage ($U_e$):** | 230 / 400 V AC |
| **Rated Short-Circuit Capacity ( $I_{cn}$ ):** | 6 kA |
| **Rated Voltage ($U_r$):** | 230 / 400 V |
| **Standards:** | EN60898-1 |
| **Tripping Characteristic:** | B |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| **Declaration of Conformity - CE:** | 2CCY451110D0601 |
| **Environmental Information:** | 2CCY000200D0201 |
| **RoHS Information:** | 2CCC451021D0201 |