TEGERA®



Extra soft unflocked PVC-glove, suitable for wet and dirty all-round-work. Retail packed.

TEGERA® 8190A

Learn more

A BARRIER BETWEEN YOU AND THE DIRT

Extra soft unflocked 0,25 mm/9,84 mil PVC-glove (Vinyl) with smooth finish. Suitable for wet and dirty all-round work. Phthalate-free. Suitable for cleaning, sanitation, decontamination, care work, and service work.

CHARACTERISTICS	FUNCTIONS
• Good fit • Comfortable • Flexible	• Waterproof • Soft • Phthalate-free

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF
Contact with dirt, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE
Wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE
Cleaning, decontamination, sanitation, service work

PRIMARY INDUSTRIES OF USE
Horeca, facilities, service

TYPE OF WORK
Light weight

CHEMICAL RESISTANCE
According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION
TYPE All-round work gloves, Chemical protection gloves - General Protection
CATEGORY Cat. III
THICKNESS 0,25 mm
LENGTH 300 mm
DEXTERITY 5
INSIDE Unflocked
GRIP DESIGN Smooth finish
COLOUR White
PAIRS PER: BUNDLE/CARTON 10/100
AQL 1.5
DISPLAY TYPE Bag with euro slot
DIPPING MATERIAL PVC (Vinyl)

COMPLIANCE
CE 0598
UKCA Cat. III
EAC

TP TC 019:2011

Information/UIS

EN ISO 374-1:2016/A1:2018 Type B
KLMPT

EN ISO 374-5:2016

EN 388:2016+A1:2018
2000X

EN ISO 21420:2020

FEATURES
Waterproof

General Protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	K	L	M	P	T
Permeation level	6	6	6	6	6
Degradation %	12,0	4,4	4,5	-5,9	13,3

SIZE		ARTICLE NUMBER	EAN
7	S	8190A-7	7340118415628
8	M	8190A-8	7340118415772
9	L	8190A-9	7340118415925
10	XL	8190A-10	7340118416076

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.