PRODUCT-DETAILS

OS32GD03

OS32GD03 SWITCH FUSE



General Information

Extended Product Type	OS32GD03
Product ID	1SCA115188R1001
EAN	6417019476308
Catalog Description	OS32GD03 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,3-pole,03 (Left Side),DIN,000,Handle and shaft not included,

ABB EcoSolutions

End of Life Instructions	1SCC311048M0201
Environmental Product Declaration - EPD	1SCC311195D0201
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Material Compliance

Conflict Minerals	9AKK108467A5658

© 2024 ABB. All rights reserved.

Reporting Template (CMRT)	
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311036M0212
Mechanical Drawings	OS63GD03.igs
Environmental Product Declaration - EPD	1SCC311195D0201
End of Life Instructions	1SCC311048M0201

Environmental

Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	112 mm
Product Net Height	112 mm
Product Net Depth / Length	121 mm
Product Net Weight	0.99 kg 2.18 lb

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	190 mm 7.5 in
Package Level 1 Height	145 mm 5.7 in
Package Level 1 Gross Weight	1.1 kg 2.5 lb
Package Level 1 EAN	6417019476308

Technical

© 2024 ABB. All rights reserved.

Cable Cross-Section	2.5 ... 25 mm²
Connecting Capacity	Stranded 2.5 … 25 mm² Flexible 2.5 … 25 mm²
Conventional Free-air Thermal Current (I_{th})	Θ = 40 °C 32 A
Conventional Thermal Current (I_{the})	Fully Enclosed 32 A
Fuse Size	NH000
Fuse System	DIN
Handle Type	Handle and shaft not included
Mounting Type	Base mounting
Number of Poles	3P
Operating Mode	Front Operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 1 W
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Rated Current (I_n)	Main Circuit 32 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-21A (I_e)	(500 V) 32 A (690 V) 32 A
Rated Operational Current AC-22A (I_e)	(500 V) 32 A (690 V) 32 A
Rated Operational Current AC-23A (I_e)	(500 V) 32 A (690 V) 32 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 7.5 kW (400 V) 15 kW (415 V) 15 kW (500 V) 18.5 kW (690 V) 22 kW
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 2.5 kiloampere rms
Standards	IEC 60947-3
Switches Operating Mechanism	03 (Left Side)
Terminal Type	Screw Terminals
Tightening Torque	3 N·m 4 N·m
Wire Stripping Length	Main Circuit 12 mm Main Circuit 0.47 in

Technical UL/CSA

Wire Stripping Length	Main Circuit 12 mm Main Circuit 0.47 in
Tightening Torque	3 N·m 4 N·m

© 2024 ABB. All rights reserved.

Certificates and Declarations

A2L Certificate – IEC	1SCC311208D0201
ATEX Certificate	No certification needed
CCC Certificate	CCC OS32-63G_ 2016.pdf
Declaration of Conformity - CE	1SCC311136D2703
DNV GL Certificate	1SCC311125D0203
UL Certificate	No certification needed

Classifications

Object Classification Code	Q
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5291 >> Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3660222

Categories

Low Voltage Products and Systems → Switches → Switch Fuses



© 2024 ABB. All rights reserved.