8000 series

Momentary or alternate action pushbutton switches

Distinctive features and specifications



- ❑ **Bushing Ø 6,35 (1/4) and Ø 11,9 (15/32)**
- ❑ **UL approved**

B2

ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :
  - silver contacts : 4A 30VDC
  - gold plated contacts : 0,4VA max. 20VAC or DC
- Initial contact resistance : 10 mΩ max.
- Insulation resistance : 1.000 MΩ min. at 500VDC
- Dielectric strength :
  1.000 Vrms 50 Hz min. between terminals
  2.000 Vrms 50 Hz min. between terminals and frame
- Electrical life : 30.000 cycles at full load

MATERIALS

- Case : diallylphthalate (DAP)
- Actuator : brass, nickel plated
- Bushing : brass, nickel plated
- Housing : stainless steel
- Contacts
  A : silver
  AD : silver, gold plated
  CD : brass, gold plated
- Terminal seal : epoxy

GENERAL SPECIFICATIONS

- Torque : 1,25 Nm (.922 Ft.lb) max. applied to nut
- Total travel : 2,70 mm (.106)
- Operating temperature : -40°C to +85°C

AGENCY APPROVAL

3A 250VAC, 6A 125VAC

Availability : consult factory for details of approved models.

Marking : to order switches marked UL, complete appropriate box of ordering format.

8000 series

Momentary or alternate action pushbutton switches

Overview

MODEL STRUCTURE

8 [ ] [ ] [ ] [ ] [ ]

SERIES

Terminals and bushings

4	Straight PC or right angle terminals
6	Solder lug terminals

All models with Ø 6,35 (1/4) or Ø 11,9 (15/32) threaded bushing.

Number of poles

3	Single pole
4	Double pole

Electrical functions

2	ON	-	MOM
6	ON	-	ON

Terminals

Blank	Solder lugs or straight PC depending on model
W	Right angle

B2

OPTIONS ● ● ●

[ ] [ ] [ ] [ ] [ ]

Order separately.

Contact materials

A	Silver
AD	Silver, gold plated
CD	Brass, gold plated

Sealing

Blank	No sealing
B	Epoxy sealed terminals
K	Front panel sealing by O-ring and sealing washer

Plungers

For bushing Ø 6,35 (1/4)

Blank	Height 6,3 (.248)
-9	Height 8,8 (.346)

For bushing Ø 11,9 (15/32)

Blank	Height 8,6 (.338)
-6	Height 7 (.275)

Special options

X718	Bushing Ø 11,9 (15/32)
X934	Flatted bushing Ø 11,9 (15/32) + front panel sealing

Other, see following pages.

Approval

UL

Availability : Consult factory for details of approved models.

Caps

U900	Ø 5 (.196)
U1140	Ø 8 (.314)
U1720	Ø 9,4 (.370)
U480	Ø 10 (.393) Standard
U630	Ø 15 (.590)
U2430	Square Height 4 (.157)
U2020	Square Height 6 (.236)

ABOUT THIS SERIES

On the following pages, you will find successively :
- model structure of switches
- options in the same order as in above chart

Dimensions : first dimensions are in mm while inches are shown as bracketed numbers.

Sealing boots are available to protect the switches against dust and water. They are presented in section H.

Mounting accessories : standard hardware supplied with all models : 2 hex nuts 8 mm (.314) across flats, 1 locking ring and 1 lockwasher.
Standard and special hardware available are presented in section I.


Packaging unit : 50 pieces, except 8000W (25 pieces).

8000 series


Momentary or alternate action pushbutton switches

Threaded bushing Ø 6,35 (1/4)

MODEL STRUCTURE




- Solder lug, straight PC or right angle terminals
- 1 and 2 pole configurations
- Button returns in upper position after actuation.



B2

MODEL STRUCTURE




Shown with standard plunger

Solder lug terminals : 8600




	2-3	1-2
Single pole		
8632	ON	MOM
8636	ON	ON
	2-3	1-2
	5-6	4-5
Double pole		
8642	ON	MOM
8646	ON	ON



Straight PC terminals : 8400




	2-3	1-2
Single pole		
8432	ON	MOM
8436	ON	ON
	2-3	1-2
	5-6	4-5
Double pole		
8442	ON	MOM
8446	ON	ON




Right angle terminals - horizontal : 8400W




	2-3	1-2
Single pole		
8432W	ON	MOM
8436W	ON	ON
	2-3	1-2
	5-6	4-5
Double pole		
8442W	ON	MOM
8446W	ON	ON



PANEL CUT-OUT



Standard



With **K** sealing option

CONTACT MATERIALS




A Silver
AD Silver, gold plated
CD Brass, gold plated

SEALING



Blank No sealing


B Epoxy sealed terminals



K Front panel sealing by one O-ring and sealing washer. Protects the switch against water and dust.
Panel seal withstands 1 bar pressure.

KB Combined sealings

Sealing boot : see section H.




① O-ring
② Sealing washer

8000 series

Momentary or alternate action pushbutton switches


OPTIONS

PLUNGERS




For Ø 6,35 (1/4) bushing

Dash compulsory before plunger code.




Blank
Standard




-9

For Ø 11,9 (15/32) bushing (X718 models)




Blank




-6

SPECIAL OPTIONS




X601 **Silver plated brass contacts**
Current/voltage rating for an electrical life of 20.000 cycles : 0,5A 30VDC.
Minimum quantity : 5.000 pieces per model and shipment.

X718 **Bushing Ø 11,9 (15/32)**
For all basic models (solder lug straight PC or right angle terminals)
Available with plungers 13 and 6.
K sealing option available.




X748 Snap-in mounting. Consult factory
Panel cut-out 15 x 12,5 (.59 x .492)

X934 Flatted bushing Ø 11,9 (15/32) + sealing by two O-rings (for plunger -6 only). Epoxy sealed terminals.



APPROVAL




UL

Availability : consult factory for details of approved models.
Marking : to order switches marked UL, complete above box with "UL".


CAPS

Order separately.


The caps below are for Ø 4 mm plungers (standard and -9), except U2600.




U900




U1140



U1720



U480
Standard




U630


Cap colours

Replace last "0" by number


1	blue	**5**	yellow
1/4	dark blue	**6**	red
2	black	**7**	ivory
3	green	**7/1**	white
4	grey	**9**	orange



U2430
Square




U2020
Square




U2600
For large plunger -6 only.

DRESS NUTS


Chrome plated. Order separately.



U1636
For cap U1140



U825
For cap U630



U840
For cap U480