

ELDE.NBL24

- **blue LED**
- **24 VAC/DC**
- **Screw connection**
- **Mounting flange position 3**

Data

Ordering data	
Product type description	ELDE.NBL24
Article number (order number)	101165999
EAN (European Article Number)	4250116200696
eCl@ss number, Version 9.0	27-37-13-02
Certifications	
Certificates	cULus CCC EAC
General data	
Product name	Light terminal block ELD
Standards	EN 60947-5-1 IEC/EN 60947-1
Installation conditions (mechanical)	arbitrarily
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	20 g
General data - Features	
Integral System Diagnostics, general	Yes
Mechanical data	
Installation instructions	pluggable
Mounting flange position	3

Mechanical data - Connection technique	
Terminal Connector	Screw connection
Terminal designations	EN 50005 EN 50013
Cable section, minimum	0.5 mm², rigid 0.5 mm², flexible
Cable section, maximum	2.5 mm², rigid 1.5 mm², flexible

Mechanical data - Dimensions	
Width	10 mm
Length	46 mm
Depth	60 mm

Ambient conditions	
Protection class of Clips or Terminals	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

Electrical data	
Rated operating voltage	250 V

Status indication	
Colour of the LED	Blue
Note (LED switching conditions display)	Supply voltage UB: 24 VAC/DC

Documents

CCC certification
(1,4 MB, 10.05.2019, Revision B)

EAC certification

Pictures

Product picture (catalogue individual photo)



ID: keldlf01

| 534,7 kB | .jpg | 352.778 x 494.594 mm - 1000 x 1402 Pixel - 72 dpi
| 64,5 kB | .jpg | 27.009 x 37.931 mm - 319 x 448 Pixel - 300 dpi
| 41,8 kB | .png | 74.083 x 103.717 mm - 210 x 294 Pixel - 72 dpi


Diagram



ID: krdlek01

| 11,4 kB | .jpg | 112.889 x 25.4 mm - 320 x 72 Pixel - 72 dpi
| 16,9 kB | .cdr |

Operating principle



ID: krf--a05

| 19,5 kB | .cdr |