POLYETHYLENE (PE) TUBING

Email Print



Parker Legris offers two types of polyethylene tubing: "Advanced PE" 50% reticulated and Low Density PE.
Our range of "Advanced PE" is designed for demanding environments, especially that of water treatment, without compromising operator safety.

PART NUMBER:
1015Y08F00

TUBE I.D. (MM):
5,75

TUBE I.D. (INCH):
na

TUBE O.D. (MM):
8

TUBE O.D. (INCH):
na

COLOR:
NATURAL

LENGTH (M):
150

LENGTH (INCH):
na

Reset Attributes

WHERE TO BUY

PRODUCT OVERVIEW

TECH SPECIFICATIONS

Print Tech Specifications

PERFORMANCE CHARACTERISTICS

MAXIMUM PRESSURE (BARG)

16

MINIMUM WORKING TEMPERATURE (°C)

-40

MAXIMUM WORKING TEMPERATURE (C)

95

VACUUM RATING (MM OF HG)

755

WEIGHT (KG/PACKAGE)

4.05

MAXIMUM BEND RADIUS (MM)

40

MAXIMUM BEND RADIUS (INCH)

na

NUMBER OF TUBES

1

APPLICATION

Beverage, Chemical, Petrochemical, Food Process, Water, Water Treatment

MEDIA

Advanced PE: Water, beverages and other fluids/Low Density PE: Industrial fluids

CERTIFICATES

Advanced PE Tubing: FDA: 21 CFR 177.1520, RG: 1935/2004/EC, DI: 97/23/EC (PED), DI: 2002/95/EC (RoHS), 2011/65/EC, NSF 42/58 (1/4" and 3/8" approved for 10 bar and 1/2" approved for 8 bar at room temperature), NSF 51, 61 C-HOT, ACS (except for purple co

Print Tech Specifications

PRODUCT SUPPORT

RECOMMENDED



ıgs and
ds



Polyamide (PA) Flexible Tubing



Fluoropolymer (PFA) Tubing



Polyurethane PU Tubing

CONTACT US

Parker Hannifin Manufacturing France SAS

Fluid System Connectors Division Europe
Parc Alcyone - Bat. D
1 rue André et Yvonne Meynier - CS 46911
35069 Rennes Cedex France

Phone
Phone: +33 (0) 2-99-25-55-00

EMAIL PARKER

Parker Hannifin

Products
About Parker
Investors
Community
Careers