PRODUCT-DETAILS

E4.2V 2500 Ekip Touch LI 3p WMP

E4.2V 2500 Ekip Touch LI 3p WMP



General Information

Extended Product Type	E4.2V 2500 Ekip Touch LI 3p WMP
Product ID	1SDA072474R1
EAN	8015644763244
Catalog Description	E4.2V 2500 Ekip Touch LI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E4.2V 2500 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/TOUCH-LI R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2363
Environmental Product Declaration - EPD	9AKK108468A1904 9AKK108468A1910
Recyclability Rate of the	Design for Closing Resource Loops - Standard EN45555 - 79.3 %

© 2024 ABB. All rights reserved.

Product acc. to EN45555

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy (IT)
Simplified SCIP	7f3be359-1216-4d35-b9d4-eab9cbb290fd Poland (PL) cc5cb3c7-f20f-4e57-a699-41c96b5a1eef Norway (NO) de6447a0-df24-4a20-8466-f5f11a930a19 Finland (FI) de9a0119-6bd3-4d97-a5d3-1e74d280ccf7 Belgium (BE) 8ad28a13-de77-4592-95fd-897a501569c8 Germany (DE) 8b03cfe9-7657-4778-acb1-5e456af5c76a Denmark (DK) 08ff7a7d-f7c4-4a97-ab1f-2f60e52ccc4e Germany (DE) 18044daa-d0c0-4608-bafb-451bb9d8efe4 Croatia (HR) 5ede7a36-3b83-4497-b7e0-ef217691ad89 Czech Republic (CZ) e5eed5bf-546a-4db4-a608-d4b83c43c056 Poland (PL) bf55e5c1-47fb-4603-bc85-150f2bba6810 Netherlands (NL) 13fc1439-00ad-45bf-abdd-5ede1ce20a7d Hungary (HU) 7635dc57-155c-4b3b-8d16-637f7a9317ca Estonia (EE) f49fce99-7561-4c32-880a-478431f7efd7 Greece (GR) 05702ea0-ab49-475f-8469-3cf48dabeb77 Portugal (PT) 8d8d3917-aca7-4875-98c5-244d35793f56 Bulgaria (BG) 64831dac-5718-413a-b2dd-c2a16236b94f Sweden (SE) 55ebef71-4502-4891-8767-e9a15ef09392 Poland (PL) a940f727-3880-42c1-bdc0-d5e1d498ddaf France (FR) 560d9c18-bf6e-4a6e-b95a-82f0dcbd0d2c Sweden (SE) f40ef067-0a7a-4928-831d-6affa0d2f0c7 Germany (DE) 6e3f01fd-be03-4be8-9d80-b02a9984a4e1 Germany (DE) 7e9377e0-b60f-471e-982f-360fb85b51c6 France (FR) 1c74a6dc-b960-484a-a4e4-4114d79c6a3d Hungary (HU) 1ac41cb5-8851-4d50-97e5-9a58e2df1d99 Spain (ES) 5b96a5ce-08d7-4ea3-9d9d-b2ed25c73f5d Belgium (BE) a16503c8-c993-4d7a-9277-704db1bb451b Germany (DE)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	Z4VUELAD000A000000XX
EAN	8015644763244
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	425 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm

© 2024 ABB. All rights reserved.

Product Net Weight	60 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	67 kg
Package Level 1 EAN	8015644763244

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W
CAD Dimensional Drawing	1SDH001252R0433

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	743 W
Rated Current (I_n)	2500 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA

© 2024 ABB. All rights reserved.

	(525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2500 A
Rated Voltage (U_r)	690 V
Release	Ekip Touch LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E4.2
Suitable for IT Networks	Yes, 690V

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5545
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001001R0102
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2





© 2024 ABB. All rights reserved.