RAL ACSB1010

- **Part # : RAL ACSB1010**
- **Hose : AIRCA 10**
- **Hose material : 2 layers of SBR / Textile braid**
- **ID. : 10 mm**
- **OD . : 18 mm**
- **Hose lenght : 10 m**
- **Working pressure : 20 bar**
- **Maxi temperature : +70°C**
- **Mini temperature : -30°C**
- **Resistance : Traction, torsion, flexion, abrasion**
- **Mounting : Calibrated ear clamp**
- **Scratch protection : ECP rubber protective boot (both ends)**
- **Coupling : CSI 061810**
- **Profile : ISO 6150 C passage 6 (Color code black)**
- **Coupling : Safety, Anti-static, non-scratch, silicon free**
- **Standards : ATEX 2, ISO 4414**
- **DAir flow @ 6 b : 833 l/min**
- **Plug : Anticorrosion treated steel**
- **Mounting : Calibrated ear clamp / Black color code ring**







PREVOST SAS – C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France
Tel. +33 (0)4 50 64 04 45 - Fax. +33 (0)4 50 64 00 10 - sales@prevost.eu - www.prevost.eu
Ce document ne peut être considéré comme contractuel. Dans un souci d'apporter un meilleur service à ses clients, la société PREVOST se réserve la possibilité de modifier les caractéristiques de sa gamme, sans préavis