JALTORNADO ESD
JVJV111

S3S CI FO SR
EN ISO 20345:2022
35 to 48



HELIUM 2

ASSEMBLÉ EN FRANCE

- **Microfiber upper**
- **PU/PU BASF® sole**
- **ESD / Dissipative**
- **Aluminum safety toe cap type B and midsole no metallic S**

- Low safety shoe urban sport type designed with **technology combining performance and lightness**, black color.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1.**
- Water-repellent microfiber upper, nubuck look. Reflective tape at the heel.
- Breathable upper lining in **3D mesh**, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the shoes.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Closed by **BOA® Fit System**, delivers micro-adjustable, precision fit engineered to perform in the toughest conditions. The **BOA® Fit System** is **guaranteed** for the lifetime of the product on which it is integrated.
- **SOFT LIGHT** hygiene insole in ultra-lightweight expanded polymer, cushions pressure points, improves weight distribution and absorbs heel impact. Anatomically shaped, perforated and equipped with the innovative **Link ESD™** multi-contact static dissipation system (Patent pending).
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- **PREM-Alu** tip in aluminium **type B** resisting an impact of an energy of 200 joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard **22568-1:2019**.
- Insole and anti-puncture midsole in non-woven **FLEX-LIGHT By Jallatte**, **54% lighter than a standard insert, complies with standard 22568-4:2021**, antistatic, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- Heel stiffener to reinforce the heel seat.
- **Innovative HELIUM sole** in bi-component **PU LIGHT/ PU** from **BASF®** , specially formulated for an incomparably light feel and absolute comfort.

Slip resistance tests results EN Standard ISO 20345:**2022**
Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,40** (≥0,31)
B- Front to back **0,38** (≥0,36)

Additionnal requirement **SR :** Ceramic /Glycerin
C - Heel to the front **0,25** (≥0,19)
D- Front to back **0,23** (≥0,22)

- Polyurethane outsole.
- **Special low-density PU comfort formulation.**
  - Lighter but just as effective as conventional polyurethane.
  - Guarantees a better 'durability/weight' ratio.
  - **Unequalled feeling of lightness.**
  - **Suitable for working environment with few constraints**.
  - Good resistance to oils and hydrocarbons.



Weight	Gross weight (42) : 1336 g / Net weight (42) : 1120 g			
Size	35 to 39	40 to 41	42 to 44	45 au 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	365 x 260 x 133
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	695 x 276 x 385

Non contractual document
Copyright JALLATTE
Limited distribution

09/06/2026

Jallatte®

www.jallatte.com