



jalas® TIO 2068

EN ISO 20345:2011 S3, SRC ASTM F2413-18 M/I/C SD 35 PR

Learn more

THREE IN ONE SOLE. TRI-PANEL BOA

A soft and water repellent safety shoe with high-quality protection. Ultimate softness and comfort thanks to the soft and stable TIO (Three In One) sole that prevents long term injuries to the feet and back. The Tri-Panel BOA® Fit System enables a soft and perfect fit for individually shaped feet. The shoe has an aluminium toe cap and soft textile nail-penetration insert. The new Three in One sole technology is developed by Jalas.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Ventilating insole
- Ergonomically shaped
- Soft
- BOA® Fit System
- Antistatic/ATEX
- Anatomically designed
- Shock absorbing
- Free from animal-derived materials

xrd PROTECTION BOA DIALED IN. PRECISION FIT. ComSoft Air

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, environments with risk for outsole penetration, slippery environments, dry environments, clean environments, warm environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION TIO
UPPER MATERIAL CPU overmolding, Microfiber, Textile
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester
INSOLE FX3 Soft
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, PU, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL RPU outsole
FASTENING BOA® Fit System
COLOUR Black, Yellow

COMPLIANCE

CE Cat. II

EN ISO 20345:2011
S3, SRC

EAC

ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Water repellent
- Nail protection in plasma-treated composite (PTC) textile

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	2068-35	6408487537936
36	3	4	5	2068-36	6408487537974
37	4	5	6	2068-37	6408487538018
38	5	5½	6½	2068-38	6408487538056
39	6	6½	7½	2068-39	6408487538094
40	6½	7½	8½	2068-40	6408487538131
41	7	8	9	2068-41	6408487538179
42	8	9	10	2068-42	6408487538216
43	9	9½	11	2068-43	6408487538254
44	10	10½	11½	2068-44	6408487538292
45	10½	11	12½	2068-45	6408487538339
46	11	12	13	2068-46	6408487538377
47	12	13	14	2068-47	6408487538414
48	13	13½	14½	2068-48	6408487538452

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.