



jalas® SPOC 5382

EN ISO 20347:2012 01, SRC, FO, A, E ASTM F2892-18 SD 35 ASTM F3445-21 SR

Learn more

FOR THE SERVICE SECTOR, WITH BOA®

A comfortable and certified occupational shoe for people in the service sector who are on their feet all day. The shoes are tested and approved for slip resistance and has shock-absorbing soles in multiple layers for personal protection. Textile fabric with high breathability makes the shoe cool, the BOA® Fit System on the side gives a perfect fit and the sock-like construction improves comfort. ESD certified for protection of sensitive electronic equipment. All models are unisex.

CHARACTERISTICS

- Excellent shock absorption
- Light
- Excellent grip
- Perfect fit
- Extra comfortable
- Breathable

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Breathable mesh
- Low weight
- BOA® Fit System

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Prevents risk of: , sprain injuries, antistatic, slipping, strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, slippery environments

PRIMARY AREAS OF USE

Care work, cleaning, healthcare, hotel- and restaurant work, office work, service work, shop work

PRIMARY INDUSTRIES OF USE

Horeca, facilities, service, retail

SPECIFICATION

TYPE Occupational footwear, Low shoes
CATEGORY Cat. II
FITTING Regular
COLLECTION SpOc
UPPER MATERIAL Textile
LINING MATERIAL Polyester
INSOLE FX2 Pro SpOc
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL EVA
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black, White
NET WEIGHT, (SIZE 42) 0.75 kg

COMPLIANCE

CE Cat. II

EAC TP TC 017:2011

EN ISO 20347:2012
01, SRC, FO, A, E

ASTM F2892-18
SD 35

ASTM F3445-21
SR

ÖNORM Z 1259

DGUV 112-191

FEATURES

Anti-static properties

Ergothan Shock Absorption System

ESD

Oil-resistant outsole

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	2½	4½	5382-35	6408487530067
36	3	3½	5	5382-36	6408487529665
37	4	4½	5½	5382-37	6408487529696
38	4½	5	6½	5382-38	6408487529726
39	5½	6	7	5382-39	6408487529757
40	6	6½	8	5382-40	6408487529788
41	7	7½	8½	5382-41	6408487529818
42	8	8½	9½	5382-42	6408487529849
43	9	9	10½	5382-43	6408487529870
44	10	9½	11	5382-44	6408487529900
45	10½	10½	12	5382-45	6408487529931
46	11	11½	12½	5382-46	6408487529962
47	12	12	13½	5382-47	6408487529993
48	13	13	14	5382-48	6408487530029

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.