Specifications

Eaton 239371



Catalog Number: 239371

Eaton Moeller® series DILM Paralleling link, for DILM17-M32

General specifications

Product Name
Eaton Moeller® series DILM paralleling link

Catalog Number
239371

EAN
4015082393717

Product Length/Depth
29 mm

Product Height
26 mm

Product Width
81 mm

Product Weight
0.029 kg

Certifications
CSA File No.: 012528
UL 508
CSA Class No.: 3211-04
UL
CSA
UL Category Control No.: NLRV
UL File No.: E36332
CE
CSA-C22.2 No. 14-05
IEC/EN 60947-4-1

Powering Business Worldwide

General

Accessory/spare part type

Connecting bridge

Product category

Accessories

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Short-circuit rating

Short-circuit current rating (basic rating)

125 A, max. CB, SCCR (UL/CSA)

5 kA, SCCR (UL/CSA)

125 A, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

10/100 kA, Fuse, SCCR (UL/CSA)

50/32 A, max. CB, SCCR (UL/CSA)

125/70 A, Class J, max. Fuse, SCCR (UL/CSA)

10/65 kA, CB, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

50/32 A, max. CB, SCCR (UL/CSA)

10/100 kA, Fuse, SCCR (UL/CSA)

125/125 A, Class J, max. Fuse, SCCR (UL/CSA)

10/22 kA, CB, SCCR (UL/CSA)

Design verification

Equipment heat dissipation, current-dependent Pvid

1.8 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0.6 W

Rated operational current for specified heat dissipation (In)

45 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Catalogs

Product Range Catalog Switching and protecting motors

SmartWire-DT Catalog

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

DA-DC-00004783.pdf

DA-DC-00004776.pdf

DA-DC-00004816.pdf

Drawings

eaton-contactors-dilm-paralleling-link-3d-drawing-005.eps

eCAD model

ETN.239371.edz

Installation videos

WIN-WIN with push-in technology

mCAD model

dil_m32_xp2.stp

dil_m32_xp2



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia