Date: 11/04/2023

DCCH2A - 0...4 bar - 2x1/4 -NPT-F - 2x1/2 -14 NPT-F

Compact differential pressure switch

Item number:	58440283	
Quantity:	1 pcs.	
Order code:	DCCH2A-BBH B-BLMZZZACZZZ	ZCA
Overview:	DCCH2A - 0...4 bar - 2x1/4 -NPT-F - 2x1/2 -14 NPT-F Compact differential pressure switch DC static and one-side pressure: 25 bar switch enclosure: aluminium,copper-free contact version: 1xSPDT, silver contact setting range: 0...4 bar Set point definition: Set Point not defined Process connection: 2x1/4 -NPT-F Electrical connection: 2x1/2 -14 NPT-F Mounting: Enclosure with plate for wall or direct mounting Diaphragm Material: Inconel 718 Brand: WIKA Instruments Italia Specifications according to data sheet: PV 35.40 Repeatability of set point: ≤ 1% of span Connection: Aluminium alloy	
Details:	Compact differential pressure switch Model DC Specifications according to data sheet: PV 35.40 Repeatability of set point: ≤ 1% of span static and one-side pressure: 25 bar Model of Differential Cell: H, for setting ranges from 400 mbar to 25 bar switch enclosure: aluminium,copper-free contact version: 1xSPDT, silver contact Unit: bar setting range: 0...4 bar Process connection: 2x1/4 -NPT-F Electrical connection: 2x1/2 -14 NPT-F Enclosure with plate for wall or direct mounting Diaphragm Material: Inconel 718 Set point definition: Set Point not defined Brand: WIKA Instruments Italia Connection: Aluminium alloy DCCH2A	

© 2023 - WIKA Instruments s.a.r.l.