



TEGERA® 12910

Learn more

PERFECT TO USE WHEN CLEANING TANKS

A super-long, high-safety glove 0,3 mm/11,8 mil with sandy finish for a secure grip. The glove protects against chemicals and is perfect to use when cleaning tanks. It is oil resistant thanks to triple PVC coating and stays soft in cold conditions. Phthalate-free.

CHARACTERISTICS

- High level of protection
- Good fit
- Durable
- Good grip
- Comfortable

FUNCTIONS

- Waterproof
- Extra long
- Protection against chemicals
- Phthalate-free
- Oil and grease resistant
- Soft

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Corrosive injuries, puncturing, abrasion injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Hvac installation, petro-chemical work, chemical work, chemical technology work, paper industry work, decontamination, sanitation, cleaning, laboratory work, fishing industry work, marine work

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves
CATEGORY Cat. III
THICKNESS 0,3* mm (*chem-layer)
LINING MATERIAL Seamless, Cotton
LENGTH 700 mm
DEXTERITY 5
GRIP DESIGN Sandy finish
COLOUR Blue
PAIRS PER: BUNDLE/CARTON 6/36
AQL 0.65
DIPPING MATERIAL PVC (Vinyl)
INNER MATERIAL SPECIFICATION Cotton
OUTER MATERIAL SPECIFICATION Polyvinyl chloride

COMPLIANCE

CE 0598

UKCA 0321

EAC

TP TC 019:2011

Information/UIS

EN ISO 374-1:2016/A1:2018 Type B
JKL

EN 374-3:2003

EN ISO 374-5:2016

EN 388:2016+A1:2018
4121X

EN ISO 21420:2020

FEATURES

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	J	K	L
Permeation level	2	6	3
Degradation %	9,5	-5,9	0,2

SIZE		ARTICLE NUMBER	EAN
7	S	12910-7	7392626074385
8	M	12910-8	7392626074392
9	L	12910-9	7392626074408
10	XL	12910-10	7392626074361
11	XXL	12910-11	7392626074378

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.