DATASHEET - CSAU-01/01-10IE

Switching Actuator 10A with input, energy measurement

Part no.	**CSAU-01/01-10IE**
	172939
EL Number (Norway)	**4560725**

General specifications

Product name	Eaton Moeller series xComfort switching actuator
Part no.	CSAU-01/01-10IE
EAN	4015081695270
Product Length/Depth	65 millimetre
Product height	18 millimetre
Product width	65 millimetre
Product weight	0.041 kilogram
Compliances	RoHS conform
Product Tradename	xComfort
Product Type	Switching actuator
Product Sub Type	None

Delivery program

Actuation function	Switching
Amperage rating	10 A
Bus system operating type	xComfort Radio frequent
Bus system product type	Actuator

Technical Data - Electrical

Rated operating voltage (Ue) - min	230 V
Rated operating voltage (Ue) - max	230 V
Switching current - max	10 A
Power supply	Mains
Output power	2300 W
Switching power - max	2300 W
Power consumption	0.25 W

Technical Data - Mechanical

Width in number of modular spacings	3
Mounting method	Flush mounted (plaster) Flush mounting
Number of inputs (binary)	1
Degree of protection	IP20

Additional information

Features	Radio frequent bidirectional Local operation/hand operation
Fitted with:	Bus connection LED indication
Functions	Bus module detachable
Suitable for	C-load

Technical data ETIM 9.0

Installation bus systems (EG000032) / Switch actuator for bus system (EC001097)

Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Switch actuator for bus system (ecl@ss13-27-14-31-25 [AKE293019])

Bus system KNX	No
Bus system KNX-RF (Radio Frequent)	No
Bus system radio frequent	Yes
Bus system LON	No
Bus system Powernet	No
Other bus systems	xComfort

Radio frequent bidirectional		Yes
Mounting method		Flush-mounted
Width in number of modular spacings		3
Local operation/hand operation		Yes
With LED indication		Yes
Number of digital inputs		1
Max. switching power	W	2300
Max. switching power LED	W	0
Output power	W	2300
Suitable for C-load		Yes
Max. number of switching contacts		1
Max. switching current	A	10
Rated current	A	10
Rated operating voltage	V	230 - 230
Different phases connectable		No
Power consumption	W	0.25
With bus connection		Yes
Bus module detachable		Yes
Min. depth of built-in installation box	mm	18
Modular expandability		No
Degree of protection (IP)		IP20

© 04/2023 by Eaton Industries GmbH