
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 14276, Tapered Roller Bearings - Single Cups - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Factors

Specifications

Series	14000
Cup Part Number	14276
Design Units	Imperial

Dimensions

D - Cup Outer Diameter	2.7170 in 69.012 mm
C - Cup Width	0.625 in 15.875 mm


ent and Fillet Dimensions

r - Cup Backface "To Clear" Radius[1]	0.050 in 1.27 mm
Da - Cup Frontface Backing Diameter	2.52 in 63.00 mm
Db - Cup Backface Backing Diameter	2.36 in 59.94 mm

Factors

e - ISO Factor[2]	0.38
Y - ISO Factor[3]	1.57
Cg - Geometry Factor[4]	0.0668

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[3] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[4] Geometry constant for Lubrication Life Adjustment Factor a3l.



IMPERIAL UNITS

TIMKEN

14276
Tapered Roller Bearings - Single Cups - Imperial

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY