TEGERA®





TEGERA® 629

Learn more

HEAT-RESISTANT, WATER-REPELLENT, CUT PROTECTION

A flexible cut protection glove, level C, with an adjustable velcro strap for the best fit. Granulated palm for best grip, latex-dipping for water resistant palm and knuckle. Withstands contact heat up to 100°C/212°F. A glove that counteracts the risk of cuts, abrasions and is suitable for work in dirty and wet environments.

CHARACTERISTICS

- Comfortable
- Good grip
- Good fingertip sensitivity
- Flexible

FUNCTIONS

- Withstands contact heat up to 100°C
- Water repellent palm and knuckle

WITH Dyneema®

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Cut injuries, abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with moisture

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, wet environments, dirty environments

PRIMARY AREAS OF USE

Building and construction, installation work, tiling, concrete work, engineering, metalwork, glass industry work, forest work, agricultural work, repair work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves
CATEGORY Cat. II
LINING MATERIAL 10 gg, Dyneema®, Glass fibre thread, Nylon, Polyester
LENGTH 220-260 mm
DEXTERITY 5
GRIP DESIGN Crinkled grip pattern
COLOUR Black, Grey
PAIRS PER: BUNDLE/CARTON 12/120
DISPLAY TYPE Bag with euro slot
FASTENING Hook-and-loop
DIPPING 3/4 dipped
DIPPING MATERIAL Latex
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) Cut resistance level C
CUT RESISTANCE (EN ISO 13997) TDM: 10.7 N
INNER MATERIAL SPECIFICATION UHMWPE (Ultra high molecular weight polyethylene), Nylon, Polyester, Glass fibre thread
OUTER MATERIAL SPECIFICATION Natural latex

COMPLIANCE

CE Cat. II

UKCA Cat. II

EAC

TP TC 019:2011

Information/UIS

LATEX

EN 407:2020 (No flame protection) X1XXXX

EN 388:2016+A1:2018 2X43C

EN ISO 21420:2020

ANSI A3 CUT

ANSI 2 ABR

Contact heat rating valid for palm area only

FEATURES

Cut protection

Water repellent

SIZE		ARTICLE NUMBER	EAN
7	S	629-7	7392626064461
8	M	629-8	7392626064478
9	L	629-9	7392626064485
10	XL	629-10	7392626064492
11	XXL	629-11	7392626064508

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.