Butoject® 898



Application

- printing industry
- laboratories
- manufacturing of paints and varnishes
- chemical industry
- metal and plastics processing
- recycling and waste disposal
- cleaning and maintenance
- fire brigades and forces

Qualities and advantages

- very good protection against extremely aggressive chemicals
- excellent wearing comfort
- very good temperature flexibility
- good mechanical resistance
- high tightness against gas

Article no. **Name**	**898** Butoject® 898
Material	butyl
Description	rolled edge smooth, powdered
Length (mm) **Total thickness (mm)**	340 -360 0,7 ± 0,10
Colour **Size**	black 8, 9, 10, 11
Classification	category III EN388 2111x; ISO 374-1/Typ A BCIKLM; ISO 374-5 Virus; EN421:2010-08





Features

- AQL ‹ 0,65
- excellent low degradation
- manufactured by Vulkoject process technology
- gastight (meets NATO requirements)
- wide shape makes it possible to wear gloves underneath
- may be reused for certain chemical groups after a special cleaning process (please consult the KCL-laboratory)
- can be combined with chemical protective clothing

www.kcl.de
sales@kcl.de

KCL GmbH
Industriepark Rhoen
Am Kreuzacker 9
36124 Eichenzell
Germany
Phone +49 6659 87-300
Fax +49 6659 87-318

by Honeywell

V0708 I 8 GB

Honeywell