

LEITZ

# Leitz iLAM Office A3 Laminator

Contemporary and compact, the Leitz iLAM Office laminating machine seamlessly integrates style and efficiency. This A3 laminator offers effortless lamination, featuring a fast 1-minute warm-up time and the ability to laminate an 80-micron A4 sheet in just 36 seconds, ensuring quick and easy document protection. The intuitive touch panel provides three pouch thickness settings for versatile use, along with an anti-jam reverse button for smooth removal of misfed pouches. The innovative SMART status LED uses lights and sounds: red during warm-up, green with an audible signal when ready, and flashing red for auto shut-off after 15 minutes of inactivity. Additionally, the SMART entry guide LEDs ensure perfect pouch alignment to prevent jams. Grey and white colour.














## Attributes

- Ready to use in just 1 minute with an ultra quick warm-up time.
- Laminates an 80-micron A4 document in approximately 36 seconds, and is also compatible with A4 high-speed pouches for enhanced productivity.
- SMART status LED: glows red during warm-up and turns green with an acoustic signal when the laminator is ready to use.
- SMART entry guide LEDs: ensure pouches feed straight through the laminator to prevent jams.
- The intuitive touch panel features an anti-jam reverse button for easy removal of misfed pouches.
- Compatible with pouches ranging from 75 to 125 microns.
- Reduce energy consumption with the 15-minute auto shut-off feature. Sensors automatically detect inactivity and power down the machine to save energy.
- Includes a starter kit of 5x A4 pouches (80 microns).
- CE certified, TUV/GS
- Recommended for use with Leitz UDT Pouches.

## Specifications

| | |
|---|---|
| Number | 72531084 |
| Colour | dark grey |
| Dimensions (W x H x D) | 470 x 102 x 144 mm |
| Laminating Speed (mm/min) | 500 |
| Temperature | 126C-143C |
| Power Supply | 220-240V AC 50/60Hz |
| Warm up Time (min) | 1 |
| Heating System | 2 from outside heated rollers |
| Operation Mode | 2 roller, no carrier, temperature controlled |
| Max. Laminating Width (mm) | 330 |
| Max. Laminating Thickness (mm) | 0.5 |
| Max. Pouch Thickness (microns) | 75-125 |
| Power Consumption (W) | 1400 |
| Dimensions (with Tray) mm | 470,00x102,00x144,00 mm |
| Anti-Jam Technology | Manual reverse button |
| Approx. lamination time (A4) | 36 secs (A4 80 micron) |
| Photo friendly | yes |
| Weight | 2350 g |
| Pallet quantity | 72 |
| EAN code | 4002432112913 |