DATASHEET - SL7-L120-B

Continuous light module; blue; LED;120 V

Part no.	**SL7-L120-B**
	171467
EL Number (Norway)	**4137721**

Product name	Eaton Moeller® series SL7 Continuous light module
Part no.	SL7-L120-B
EAN	4015081677948
Product Length/Depth	73 millimetre
Product height	73 millimetre
Product width	73 millimetre
Product weight	0.082 kilogram
Compliances	CE Marked
Certifications	CSA Certified CSA Std. C22.2 No. 94-91 cULus Listed IEC Rated UL 508 UL Listed file E29184 CSA Class No. NKCR7 CSA Std. C22.2 No. 14-10 UL Listed UL File No.: E29184 Certified by UL for use in Canada CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 CSA-C22.2 No. 94-91 UL Category Control No.: NKCR UL CE UL report applies to both US and Canada CSA Class No.: NKCR7 IEC/EN 60529
Product Tradename	SL7
Product Type	Continuous light module
Product Sub Type	None
Catalog Notes	0
Color	Blue
Enclosure color	Black
Functions	Continuous light
Light modules	LED
Number of modules	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
Connection to SmartWire-DT	No
Current consumption	0.028 - 0.031 A, at 110/120 V AC
Degree of protection	NEMA 4X IP66
Lifespan, electrical	100,000 h
Light type	Continuous light
Material	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Type	Continuous light module

Voltage type		AC
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Leakage current		0.003 A
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - min		110 V
Rated operational voltage (Ue) at AC - max		120 V
Rated operational voltage (Ue) at DC - min		0 V
Rated operational voltage (Ue) at DC - max		0 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])

Function		Continuous light
Colour		Blue
Outer diameter	mm	73
Operating voltage at AC 50 Hz	V	110 - 120
Operating voltage at AC 60 Hz	V	110 - 120
Operating voltage at DC	V	0 - 0
Voltage type		AC
Lamp type		LED
Colour housing		Black
Degree of protection (IP)		IP66
Degree of protection (NEMA)		4X

© 04/2023 by Eaton Industries GmbH