Specifications

Eaton 206899

Catalog Number: 206899

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=280x200x125mm, +mounting plate



General specifications

Product Name
Eaton Moeller® series CI-K Insulated enclosure

Catalog Number
206899

EAN
4015082068998

Product Length/Depth
280 mm

Product Height
125 mm

Product Width
200 mm

Product Weight
1.33 kg

Certifications
IEC/EN 60529
IEC 60068-2-11
UL94: HB
UL94: VO/1.5 mm thickness
DIN EN 62208

Catalog Notes
Lamp indicator L-... can be mounted in base knock-out M20/M25

Powering Business Worldwide

Product specifications

Type

Basic enclosure

Features

Halogen free

UV resistance beneath protective shield

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Not applicable.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Resources

Declarations of conformity

UKCA CI-K..-TS/M general purpose enclosures

CE CI-K..-TS/M general purpose enclosures

Drawings

eaton-insulated-boards-mounting-ci-k-insulated-enclosure-dimensions-012.eps

eaton-insulated-boards-enclosure-ci-k-insulated-enclosure-dimensions.eps

eaton-small-enclosures-enclosure-ci-k-insulated-enclosure-dimensions-009.eps

eCAD model

ETN.CI-K5-125-M

Installation instructions

IL01502081Z

mCAD model

ci_k5_m

ci_k_m_9

Meets the product standard's requirements.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

Fitted with:

Control cable entry
DIN-rail
Weight of fitted components: max. 1.7 kg

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78

Enclosure material

1 Ω x 10^{13} (Surface resistance to IEC 60093)
Plastic

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

35 W

Heat dissipation per pole, current-dependent Pvid

0 W

Mounting depth

98 mm

Mounting weight capacity - max

1 kg

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

Product category

Empty enclosures

Enclosure color

Light gray, Cover (RAL 7035)
Light gray, Operator (RAL 7035)
Black (RAL 9005)

Environmental resistance

Partly resistant to alcohol
Partly resistant to benzene
Resistant against gasoline
Resistant against greases
Chemical resistant (Base, Cover)
Not resistant to alkalis
Partly resistant to greases
Resistant against benzene
Not resistant to Mineral oil
Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material)
Resistant against alkalis
Not resistant to benzene
Partly resistant to acids (> 10%)
Resistant against alcohol
Resistant against salt solutions
Resistant against acids (< 10%)
Resistant against mineral oil

Cover material

Glass-fiber reinforced polycarbonate

Degree of protection

IP65
NEMA Other

Model

Surface mounting

Dielectric strength

30 kV/mm, according to IEC 60243-1

Degree of protection (front side)

IP65

Temperature resistance

-40 - 120 °C (enclosure)

-40 - 80 °C (gasket)

Suitable for

Emergency stop

Flammability characteristics

960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2)

650 °C/1 mm thick (push-through membrane) to VDE 0471 Part 2)

Knockouts

Metric cable entry knockouts at the top, bottom and back plate

Hard knockout version

Impact resistance

IK06 (according to EN 50102)

Radiated heat dissipation with separate mounting

35 W (at an ambient temperature of 20 °C)

Surface treatment

Resistant to corrosion

Track resistance

CTI 175 (base, to IEC 60112)

CTI 175 (cover, to IEC 60112)

Water consumption

0.29 % (According to DIN EN ISO 62)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia