PRODUCT-DETAILS

SPLHCB20/25M

20MM GS-TPR COND SS BRD 25M-BL



General Information

Extended Product Type:	SPLHCB20/25M
Product ID:	7TCA296100R0170
EAN:	5020963011955
Catalog Description:	20MM GS-TPR COND SS BRD 25M-BL
Long Description:	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Overbraid, Medium Flexibility, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black
Display Name:	SPLHCB20/25M

Additional Information

Product Main Type:	Adaptaflex Flexible Cable Protection
Application:	Liquid Tight - Extreme Temperature Environments

Ordering

© 2026 ABB. All rights reserved.

EAN:	5020963011955
UPC:	786210245508

Dimensions

Outside Diameter:	21.1 mm

Technical

Number of Batteries:	0
Color:	Black
Material:	Galvanized Steel Core with Thermoplastic Rubber Cover

Environmental

WEEE Category:	Product Not in WEEE Scope
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	5020963011955
Package Level 1 Height:	8 in 203 mm
Package Level 1 Depth / Length:	16 in 406 mm
Package Level 1 Width:	16 in 406 mm

Certificates and Declarations

Declaration of Conformity - CE:	9AKK107492A9618
RoHS Declaration:	9AKK107992A8994
REACH Declaration:	9AKK107992A8994

External Classifications and Standards

ETIM 8:	EC001179 - Protective metallic hose
ETIM 9:	EC001179 - Protective metallic hose
UNSPSC:	39131706

© 2026 ABB. All rights reserved.

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems



© 2026 ABB. All rights reserved.