Date: 22/04/2024

PCS2MC 0,5 … 2,5 bar Adaptor G 1/4 -F, Cable gland armoured , nickel-plated brass

Compact Pressure Switch

Item number: 48743112

Quantity: 1 pcs.

Order code: PCS2MC-BACC-68SZZZ1ZZ ZCKW
B000100IZZZZZZZZZ
F4-C1- - - - -

Overview:
PCS2MC 0,5 … 2,5 bar Adaptor G 1/4 -F, Cable gland armoured , nickel-plated brass
Compact Pressure Switch
PCS
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, gold-plated contact, hermetically sealed with argon gas
Setting range, working range, proof pressure: 0,5 … 2,5 bar, working range -1 … 10 bar, proof pressure 40 bar
Process connection: Adaptor G 1/4 -F
Electrical connection: Cable gland armoured , nickel-plated brass
standard direct or wall mounting, fixing bore on the case

Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 1.00 bar increasing,

Approvals / Certificates
IECEx-ATEX Ex ia

Details:
Compact Pressure Switch
Model PCS
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
1xSPDT, gold-plated contact, hermetically sealed with argon gas
0,5 … 2,5 bar, working range -1 … 10 bar, proof pressure 40 bar
Process connection: Adaptor G 1/4 -F
Electrical connection: Cable gland armoured , nickel-plated brass
standard direct or wall mounting, fixing bore on the case

© 2024 - WIKA Instruments s.a.r.l.

Approvals / Certificates: with
Switch standard: without
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCS2MC 0,5 … 2,5 bar
1. set point: 1.00 bar increasing,

Approvals / Certificates
IECEx-ATEX Ex ia

© 2024 - WIKA Instruments s.a.r.l.