890 Permanent/Traffic Light Beacon



Permanent Beacon

- **Permanent Beacon for traffic light combinations**
- **Innovative fixing bracket for simple mounting**
- **Also with two bulb sockets for uniform safety, even in the case of bulb failure**

TECHNICAL SPECIFICATIONS:

Dimensions (Ø x Height):	150 mm x 154 mm
Housing:	PC/ABS-Blend, grey
Lens:	PC, transparent
Socket:	E27 max. 25 W at 890 X00 00 2 sockets each with max. 15 W at 890 X10 00 with adhesive stickers E27 max. 15 W
Fixing:	Base mounting, fixing bracket (accessory), tube mounting (accessory)
Connection:	Screw-free clamp mechanism max. 1.5 mm²
Cable entry:	From top or bottom with cable gland M 20 x 1.5 mm or from the back with rubber grommet Ø 6-12 mm, included in assembly



Traffic Light Combination with mounting bracket (accessory)

ORDER SPECIFICATIONS:

PERMANENT BEACON

Voltage	12 – 240 V≂
red	**890 100 00**
green	**890 200 00**
yellow	**890 300 00**
clear	**890 400 00**
blue	**890 500 00**

PERMANENT BEACON WITH 2 SOCKETS (INCL. REFLECTOR)

Voltage	12 – 240 V≂
red	**890 110 00**
green	**890 210 00**
yellow	**890 310 00**

Further colours and voltages on request.



Permanent beacon with two sockets

ADDITIONAL INFORMATION:

Please also see LED Beacon/LED Traffic Light 890 with additional advantages (see p. 159)

- Maintenance-free LED technology
- Life duration up to 50,000 hrs
- Clear signalling effect even in direct sunlight





WERMA SIGNALTECHNIK



NEW **Beacon 890 in combination with Multi-Tone Sounder 190 (see page 228)**



NEW **The new adaptor (accessory) allows quick and simple mounting on a tube (Ø 75 mm)**



890 with adhesive sticker (accessory)

ACCESSORIES:

FIXING BRACKET

Fixing bracket for one beacon	**975 890 33**
Fixing bracket for two beacons	**975 890 34**
Fixing bracket for three beacons	**975 890 35**
Fixing bracket for four beacons	**975 890 37**

Mounting material and connecting grommet included in assembly.
Further information can be found on page 162.

CONNECTING GROMMET

Connecting grommet for traffic light combinations	**975 890 25**

NEW

TUBE ADAPTOR

Adaptor for tube mounting (suitable for Ø 75 mm tubes)	**975 890 36**

REFLECTOR

Additional reflector for 890 X00 00	**975 890 02**

BULBS

LED bulb E27, 24 V	**956 X20 75**
LED bulb E27, 115 V	**956 X20 67**
LED bulb E27, 230 V	**956 X20 68**

X see page 167.

Bulb E27, 24 V / 25 W	**955 890 55**
Bulb E27, 115 V / 25 W	**955 890 67**
Bulb E27, 230 V / 25 W	**955 890 68**
Bulb E14, 230 V / 15 W	**955 890 38**

ADHESIVE STICKERS:

→	**975 890 52**
STOP	**975 890 53**
START	**975 890 54**
KEIN ZUTRITT	**975 890 56**
ZUTRITT	**975 890 55**
BETRIEB	**975 890 57**
STÖRUNG	**975 890 58**
↯	**975 890 64**
✋	**975 890 65**



TECHNICAL DIAGRAMS:

see page 291