# Geberit Mapress Copper adaptor socket



Example image




## APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For connecting non-system copper pipe diameters
- For transitions from copper pipes to mild steel pipes
- For technical building systems, industry and shipbuilding

## CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- ø 14 mm to be pressed with Geberit Mapress pressing jaw ø 15 mm
- ø 16 mm should be pressed with the Geberit Mapress pressing jaw ø 18 mm
- Seal ring made of CIIR, black
- O-ring made of EPDM
- Pressing socket with transparent protection plug

## TECHNICAL DATA

| | |
|---|---|
| Product material | Gunmetal / lead-free gunmetal |

| Art. no. | DN | d, ø mm | d1, ø mm | Product material | L cm | Z cm |
|---|---|---|---|---|---|---|
| These articles are suitable for the following system: **Geberit Mapress Therm** | | | | | | |
| **62020** | 12 | 15 | 14 | Lead-free gunmetal | 4.1 | 0.1 |
| **62022** | 12 | 15 | 16 | Lead-free gunmetal | 4.1 | 0.1 |
| **62024** | 15 | 18 | 16 | Lead-free gunmetal | 4.1 | 0.1 |

| Art. no. | DN | d, ø mm | d1, ø mm | Product material | L cm | Z cm |
|---|---|---|---|---|---|---|
| These articles are suitable for the following system: **Geberit Mapress Copper** | | | | | | |
| **62020** | 12 | 15 | 14 | Lead-free gunmetal | 4.1 | 0.1 |
| **62022** | 12 | 15 | 16 | Lead-free gunmetal | 4.1 | 0.1 |
| **62024** | 15 | 18 | 16 | Lead-free gunmetal | 4.1 | 0.1 |