3106 - EQUAL AND UNEQUAL TUBE TO TUBE CONNECTOR



maximum working pressure	20 bar 2 MPa 290 psi
working temperature	-20 to 80 °C -4 to 176 °F 253 to 353 °K
vacuum capability	755 mm Hg
body	TECHNICAL POLYMER
'O'-rings	NBR
gripping ring	STAINLESS STEEL

inch Part numbers | Convert to inch | Convert to oz | Reset Filters

Part Nb	ØD (MM)	ØD1 (MM)	ØG (mm)	L (mm)	(kg)
	All	All	All	All	All
3106 03 00	3	3	8.5	25	.002
3106 03 04	3	4	8.5	25	.002
3106 04 00	4	4	8.5	25	.001
3106 04 06	4	6	11	28	.002
3106 04 08	4	8	13.5	38	.005
3106 04 56	4		11	29.5	.005
3106 06 00	6	6	10.5	28.5	.002
3106 06 08	6	8	13.5	38	.005
3106 06 10	6	10	16	42	.008
3106 06 56	6		13.5	36	.009
3106 08 00	8	8	13.5	38	.004
3106 08 10	8	10	16	42	.007
3106 08 12	8	12	19	50.5	.026
3106 10 00	10	10	16	42	.005
3106 10 12	10	12	19	50.5	.018
3106 12 00	12	12	19	50.5	.009
3106 12 14	12	14	22	56	.025
3106 12 16	12	16	27	61	.066
3106 12 62	12		22	56.5	.041
3106 14 00	14	14	22	56	.014
3106 16 00	16	16	27	60.5	.041