Rittal – The System.

Faster – better – everywhere.

Component shelf for frame attachment Enclosure width 600 and 800 mm – DK 7465.035


Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Component shelf for frame attachment Enclosure width 600 and 800 mm – DK 7465.035

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Design:	Slotted
Description:	For frame attachment, for installation in enclosures without 482.6 mm (19") accommodation.
Benefits:	Mounting bolts or mounting rails may be installed on a 25 mm pitch pattern in the enclosure depth. Mounting hole for handles provided.
Applications:	For installation in enclosures without 482.6 mm (19") accommodation
Material:	Sheet steel
Surface finish:	Spray-finished
Colour:	RAL 7035
Assembly instruction:	Additionally, two punched sections with mounting flanges are required for the inner mounting level
Supply includes:	Component shelf, slotted 2 mounting rails
Note:	Max. depth of component shelves = Enclosure depth - 100 mm.

Product description

To fit:	Enclosure type: VX Enclosure type: TS Width: 600 mm
Dimensions:	Width: 471 mm Height: 45 mm Depth: 500 mm
Installation options:	Static installation: Component shelf, 50 kg with fixing bolts on punched section without mounting flange Static installation: Component shelf, 100 kg with mounting rails on punched sections without mounting flange Depth variable: Component shelf, 50 kg with telescopic slides on punched sections without mounting flange
Load capacity:	100 kg area load
Packs of:	1 pc(s).
Weight/pack:	6.71 kg
Copper weight (kg per piece):	0
EAN:	4028177165984
Customs tariff number:	94039010
ETIM 7.0:	EC002620
ETIM 6.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 6.0/6.1:	27189261
Product description:	DK Component shelf, WHD: 471x45x500 mm, 100 kg, For frame attachment, For W: 600 mm, RAL 7035

Approvals

Certificates:	NA