HR703CD110

11-PIN Industrial relay with LED state indicator and mechanical actuator, 110VDC, 10A, 3 C/O contacts, fitting on socket HR7XS2



Product designation			11-PIN INDUSTRIAL RELAYS
Product type designation			HR704C
Contact characteristics			
Contact configuration			3 C/O
Rated insulation voltage Ui IEC/EN		V	250
Rated impulse withstand voltage Uimp		kV	6
IEC Conventional free air thermal current Ith		A	10
Rated current (In)		A	10
Relay control voltage		V	110VDC
Rated operating power AC-1		VA	2500
Rated operating power AC-15	230 VAC	VA	500
Single-phase motor control	230VAC	kW	1.2
Rated operating current DC-1	30V	A	10
Minimum switching load		V / mA	5 / 100
Contact impedance		mΩ	100
Contact material			Ag/Ni
Operating times			
Closing		ms	<30
Opening		ms	<30
Operations			
Mechanical life		cycles	5000000
Electrical life AC1		cycles	100000
Coil characteristics			
Average coil consumption AC at 20°C		VA	3
Average coil consumption DC at 20°C		W	1.5
Operating range	Closing	% Un	75…110
	Opening	% Un	10…30
Maximum cycle frequency		cycles/h	3600
Mechanical features			
Max socket terminal tightening torque		Nm	0.6
Socket screw tightening tool (cross / flat blade)			PH1 / 4.5mm
Conductor section			
AWG/Kcmil			
	min		20
	max		14
IEC			
	min	mm²	0.5
	max	mm²	2.5


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

HR703CD110


11-PIN Industrial relay with LED state indicator and mechanical actuator, 110VDC, 10A, 3 C/O contacts, fitting on socket HR7XS2


Operating position			normal	Any
Fixing				On 35mm DIN rail and with screw
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-40
		max	°C	+55
	Storage temperature			
		min	°C	-40
		max	°C	+70
Other features				
Indication				Yes
Mechanical contact position indicator				Yes
Mechanical test actuator				Yes

Dimensions



Wiring diagrams





The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Certifications and compliance

Compliance	
	IEC/EN 61810
Certificates	
	CSA
	cURus
	EAC

ETIM classification

ETIM 8.0	EC001437 - Switching relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding