DATASHEET - M30C-FL-A

Indicator light, RMQ-Titan, Flat, orange, Metal bezel

Part no.	**M30C-FL-A**
	183286
EL Number (Norway)	**4315655**

Product name	Eaton Moeller® series M30 Indicator light
Part no.	M30C-FL-A
EAN	4015081782277
Product Length/Depth	36 millimetre
Product height	32 millimetre
Product width	46 millimetre
Product weight	0.035 kilogram
Certifications	VDE 0660 IEC/EN 60947
Product Tradename	M30
Product Type	Indicator light
Product Sub Type	None
Bezel color	Chrome
Bezel material	Metal
Design	Flat
Fitted with:	Front ring
Lens color	Orange
Degree of protection	NEMA 4X, 13
Degree of protection (front side)	IP67/IP69K
Opening diameter	30 mm
Overvoltage category	III
Pollution degree	3
Product category	RMQ-Titan
Rated impulse withstand voltage (Uimp)	4000 V AC
Size	Front dimensions: Ø 36 mm
Type	Indicator lights
Mounting position	As required
Shock resistance	Not planned
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacity	0.5 - 1.5 mm², solid 0.5 - 1.5 mm², stranded
Rated insulation voltage (Ui)	250 V
Connection to SmartWire-DT	With SWD-RMQ connections Yes
Force for positive opening - min	0 N

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for indicator light (EC000223)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for warning lights (ecl@ss10.0.1-27-37-12-11 [AKF029014])			
Suitable for number of built-in signal lights			1
Colour lens			Orange
Construction type lens			Round
Hole diameter		mm	30
Width opening		mm	0
Height opening		mm	30
With front ring			Yes
Material front ring			Metal
Colour front ring			Chrome
Type of lens			Flat
Degree of protection (IP), front side			IP67/IP69K
Degree of protection (NEMA)			4X, 13

© 04/2023 by Eaton Industries GmbH