DATASHEET - KSX-3P-MID

Busbar support, TTT center, KSX

Part no. **KSX-3P-MID**
138360

General specifications

Product name			Eaton xEnergy Light LV systems LV switchgear
Part no.			KSX-3P-MID
EAN			4015081351404
Product Length/Depth			300 millimetre
Product height			300 millimetre
Product width			30 millimetre
Product weight			4.58 kilogram
Compliances			RoHS conform
Product Tradename			xEnergy Light
Product Type			LV systems
Product Sub Type			LV switchgear
Public Consumption			Yes
Product Family Description			ES-PMCC-PDC-Eaton xEnergy Light LV systems LV switchgear
Globally Marketable			Yes

Product Specification Details

Busbar distance			0 mm
Current rating - max			3200 A
Functions			KSX busbar support, central Busbar support
Number of poles			Three-pole
Rated operation current (Ie)			3200 A
Special features			For central use in xEnergy type-tested power distribution systems and XVTL distribution panel Including fixing material
Suitable for			Three-pole
Type			Distribution board feeder system KSX-System
Used with			Triple T profile Distribution board feeder system KSX-System

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Busbar support (EC001166)

Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar carrier (ecl@ss13-27-40-06-07 [ACO377016])

Number of poles			3
Max. rated current		A	3200
Busbar distance		mm	0

© 04/2023 by Eaton Industries GmbH