# HDMI CONVERTERS
## HDMI to Composite Converters

The HDCOMPOSITE-02 is designed to convert a digital HDMI signal into an analogue composite video signal with stereo audio. It allows you to use modern source equipment with older display devices that do not have a HDMI input. Power will be supplied via the DC port by using the included USB power cable.




## Specifications

**Input / Output Connector**
- Input ConnectorHDMI
- Output Connector3RCA (CVBS & L/R Analogue Audio)

**Input Resolutions (HDMI)**
- Progressive (50 & 60Hz)480p, 576p, 720p & 1080p
- Interlaced (50 & 60Hz)480i, 576i & 1080i

**Output Resolutions (CVBS)**
- Progressive480i (NTSC) @ 3.58MHz
- Interlaced576i (PAL) @ 4.43MHz

- Size (L-W-H)102x 100x 25mm
- Weight (Net)295g

## Package Contents
- 1x Converter unit
- 1x USB power cable
- 1x User manual

## Features
- Supports HDMI input, composite video and uncompressed R/L audio output
- Supports HDMI input resolutions up to 1080p @ 60HZ
- Supports analogue composite video output up to 480i (NTSC) or 576i (PAL)

| CODE | DESCRIPTION |
|---|---|
| HDCOMPOSITE-02 | HDMI to Composite Converter |