OABP304013TE

Terminal box, 300x400x132

This ABS terminal box range, OABP, with a IP 66, 67 protection degree, can be extended in depth. It is available off the shelf in many different sizes. Deeper components may be installed when an extension frame, OPCP-EE, is used. The OABP range is well suited for demanding environments, since water and dust are prevented from entering the terminal box, thus eliminating the risk for component failure, and with that unnecessary downtime.

Feature:
IP 66,67 IK 06/07

CE UKCA GOST



CHARACTERISTICS	
Note	With transparent cover
Height	300 mm
Width	400 mm
Depth	132 mm
Inner depth (mm)	115
Weight (kg)	2.40

Item no.: OABP304013TE
EAN no.: 6418677198519

Technical data

Description: ABS box, halogen-free, suitable for indoor use. Low UV radiation resistance.

Material: Body: ABS. Plain cover: ABS. Transparent cover: polycarbonate.

Gasket: Polyurethane gasket integrated in the box cover.

Temperature resistance: -40 °C to +60 °C.

Flammability: UL94 HB.

Protection: IP 66, 67 | IK 06 (-25 °C), IK 07 (+35 °C).

Finish: RAL 7035.

Delivery: Body, cover, cover screws manufactured from polyamide and mounting screws.

Features

Feature: ABS terminal box, available in a wide range of sizes, that can be extended in depth, with a high IP 66, 67 protection degree.

Advantage: Customers can choose terminal boxes that meet their size requirements, off the shelf. The installed components inside the terminal box will be safe and secure due to the high protection degree.

Benefit: Customers can receive terminal boxes with a short delivery time, that match their size requirements. This will also remove any extra costs due to oversizing. Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box. If necessary, deeper components can be installed when the expansion frame, OPCP-EE, has been mounted.

Comment:	The mounting plate, OMP, and DIN profiles, DR, have to be ordered separately, in order to complete the installation of the terminal box. The expansion frame, OPCP-EE, should be ordered if a deeper terminal box is required.