RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire)

RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire)

Item number:	48779543
Quantity:	1 pcs.
Order code:	RLS-30004M103050ZZZZZZZZZZZZ3ZZZZZ1EN8M035004Z3 Z1W101ARS3ZL6
Overview:	RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire) Magnetic float switch with temperature output Model RLS-3000 Output signal level: 1 switching output max. switching power: n.o./n.c.: AC 100 V; 10 VA; 0,5 A / DC 100 V; 10 W; 0,5 A max. switching power: Changeover/SPDT: AC 100 V; 5 VA; 0,25 A / DC 100 V; 5 W; 0,25 A Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 305.0 Switch position - Switch output 2: without Switch position - Switch output 3: without Output signal temperature: Pt100 (2-wire) Electrical connection: Cable outlet PUR, IP67 Cable length: 5 m / 16.4 ft pin assignment el. connection: see product label Process connection: G 1, installation from outside Guide tube length: 350 mm mm medium temperature: -30 °C ... 80 °C Float: Cylindrical float Ø 30 mm, 1.4571, PN10 Wetted parts: Stainless steel 1.4571 Specifications according to data sheet: LM 50.06
Details:	RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire) Magnetic float switch with temperature output Model RLS-3000 Output signal level: 1 switching output max. switching power: n.o./n.c.: AC 100 V; 10 VA; 0,5 A / DC 100 V; 10 W; 0,5 A max. switching power: Changeover/SPDT: AC 100 V; 5 VA; 0,25 A / DC 100 V; 5 W; 0,25 A Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 305.0 Switch position - Switch output 2: without Switch position - Switch output 3: without Output signal temperature: Pt100 (2-wire) Electrical connection: Cable outlet PUR, IP67

© 2023 - WIKA Instruments s.a.r.l.

Cable length: 5 m / 16.4 ft
pin assignment el. connection: see product label
Process connection: G 1, installation from outside
Guide tube length: 350 mm mm
medium temperature: -30 °C ... 80 °C
Float: Cylindrical float Ø 30 mm, 1.4571, PN10
Wetted parts: Stainless steel 1.4571
Specifications according to data sheet: LM 50.06

© 2023 - WIKA Instruments s.a.r.l.