Specifications

Eaton 120853



Catalog Number: 120853

Eaton Distribution parts. Installation contactor, 230VAC, 2N/O, 25A

General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	120853
EAN	**Product Length/Depth**
4015081186839	65 mm
Product Height	**Product Width**
85 mm	17.7 mm
Product Weight	**Compliances**
0.14 kg	RoHS conform

Powering Business Worldwide

Product specifications

Amperage Rating

25 A

Features

Additional equipment possible

Degree of protection

IP40

Equipment heat dissipation, current-dependent

7.2 W

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-40 °C

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Incandescent lamp load - max

3000 W

Load fluorescent lamp - max

1160 VA

Load fluorescent lamp (duo circuit) - max

2552 VA

Load fluorescent lamp (parallel compensated) - max

1044 VA

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

2

Number of modular spacings

1

Rated operating voltage (Ue) - max

440 V

Rated operating voltage (Ue) - min

440 V

Rated operational current for specified heat dissipation (In)

Resources

Declarations of conformity

DA-DC-03_Z-S_SC_SB

DA-DC-03_Z-SCH

DA-DC-03_Z-SC

DA-DC-03_Z-S

Drawings

eaton-wiring-diagram-z-sch-klem-bez4.jpg

eaton-3d-drawing-z-r-sch-einbau.jpg

eaton-3d-drawing-sch-pack.jpg

eaton-dimensions-ma-sch40.jpg

25 A

Static heat dissipation, non-current-dependent

0 W

Utility category

1

Voltage rating (excitation) - max

253 V

Voltage rating (excitation) - min

195.5 V

Built-in depth

60 mm

Voltage type

AC

Utilization category (according to EN IEC 60947-4-1)

AC-1

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia